

SPECIFICATIONS

Model name	EVO-X12
System Type	Passive
Configuration	2-way
Frequency Response (+/-3dB)	55Hz-20kHz
Frequency Range (-10dB)	50Hz-20kHz
Sensitivity (2.83v/1m)	98dB
System rated impedance	8Ω
Calculated Maximum SPL @1m	129dB
Low Frequency Transducer	
Size	305mm / 12"
Voice coil size	51.6mm / 2"
Rated impedance	8Ω
LF Power (re:AES-2012)	300w
Hi Frequency Transducer	
HF Driver type	Compression driver
Voice coil size	44.5mm / 1.75"
Exit size	25mm / 1"
Diaphragm Material	Titanium
Rated impedance	8Ω
HF Power (re:AES-2012)	40w
Nominal coverage	90° x 60°
Power	
System continuous power	300w
System programme power	600w
System peak power	1200w
Crossover Frequency	2.3kHz
Input connectors	2 x NL4 (speakON Compatible) + 2 x 1/4" Jacks
Hardware	
Pole mount	Dual Angle (0° or 10°) 35mm Pole Socket
Handles	2 on sides
Enclosure	
Enclosure material	MDF
Finish	Rhino rock black paint
Grille material and finish	1.2mm Steel
Dimensions - unpacked	
Height	590mm / 23.23"
Width front	430mm / 16.93"
Width rear	297.5mm / 11.71"
Depth	370mm / 14.57"
Dimensions - packed	
Height	655mm / 25.79"
Width front	492mm / 19.37"
Width rear	328mm / 12.91"
Depth	408mm / 16.06"
Weight	
Net weight	19.2kg / 42.2lbs
Gross weight	22.4kg / 49.3lbs