

HARDWARE FEATURES

Standards and Protocols	IEEE 802.3i IEEE 802.3u IEEE 802.3ab IEEE 802.3x IEEE 802.1p
Interface	8 10/100/1000Mbps RJ45 Ports (Auto Negotiation/Auto MDI/MDIX)
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) 100BASE-TX/1000BASE-T: UTP category 5, 5e or above cable (maximum 100m)
Fan Quantity	Fanless
Power Supply	100-240VAC, 50/60Hz
Power Consumption	Maximum: 4.1W
Dimensions (W x D x H)	11.6 x 7.1 x 1.7 in. (294 x 180 x 44 mm)
Mounting	13" or 19" Rack Mountable
Max Power Consumption	4.3W
Max Heat Dissipation	14.67BTU/h

PERFORMANCE

Switching Capacity	16Gbps
Packet Forwarding Rate	11.9Mpps
MAC Address Table	4K
Jumbo Frame	16KB
Transfer Method	Store-and-Forward

SOFTWARE FEATURES

Advanced Features	MAC address auto-learning and auto-aging IEEE802.3x Flow control 802.1p/DSCP QoS
-------------------	--

OTHERS

Certification	FCC, RoHS
Package Contents	8-Port Gigabit Desktop Switch Power Cord Installation Guide Rackmount kit Rubber Feet
Environment	Operating Temperature: 0°C~40°C (32°F~104°F); Storage Temperature: -40°C~70°C (-40°F~158°F); Operating Humidity: 10%~90% non-condensing; Storage Humidity: 5%~90% non-condensing