

## HARDWARE FEATURES

Standards and Protocols	IEEE 802.3i, IEEE 802.3u, IEEE 802.3x
Interface	24 10/100Mbps RJ45 Ports (Auto Negotiation/Auto MDI/MDIX)
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) 100BASE-TX: UTP category 5, 5e or above cable (maximum 100m)
Fan Quantity	Fanless
Physical Security Lock	Yes
Power Supply	100-240VAC, 50/60Hz
Power Consumption	Maximum: 3.2W
Dimensions ( W x D x H )	17.3*7.1*1.7 in. (440*180*44 mm)
Mounting	Rack Mountable
Max Power Consumption	3.19W(220V/50Hz)
Max Heat Dissipation	10.88BTU/h

## PERFORMANCE

Switching Capacity	4.8Gbps
Packet Forwarding Rate	3.57Mpps
MAC Address Table	8K
Buffer Memory	2Mb
Advanced Functions	Green Technology 802.3X Flow Control
Green Technology	Innovative energy-efficient technology saves power up to 75%
Transfer Method	Store-and-Forward

## OTHERS

Certification	FCC, RoHS
Package Contents	24-Port 10/100Mbps Rackmount Switch Power Cord Installation Guide Rackmount Kit Rubber Feet
System Requirements	Microsoft® Windows® 8, 7, Vista™, XP or MAC® OS, NetWare®, UNIX® or Linux.
Environment	Operating Temperature: 0°C~40°C (32°F~104°F); Storage Temperature: -40°C~70°C (-40°F~158°F); Operating Humidity: 10%~90% non-condensing; Storage Humidity: 5%~90% non-condensing