

## HARDWARE FEATURES

Standards and Protocols	IEEE 802.3i, IEEE 802.3u, IEEE 802.3x
Interface	16 10/100Mbps RJ45 Ports (Auto Negotiation/Auto MDI/MDIX)
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) 100BASE-TX: UTP category 5, 5e or above cable (maximum 100m)
Fan Quantity	Fanless
Physical Security Lock	Yes
Power Supply	100-240VAC, 50/60Hz
Power Consumption	Maximum: 2.1W
Dimensions ( W x D x H )	11.6×7.1×1.7 in. (294×180×44 mm)
Mounting	Rack Mountable
Max Power Consumption	2.06W(220V/50Hz)
Max Heat Dissipation	7.03BTU/h

## PERFORMANCE

Switching Capacity	3.2Gbps
Packet Forwarding Rate	2.38Mpps
MAC Address Table	8K
Buffer Memory	2Mb
Advanced Functions	Green Technology 802.3X Flow Control
Green Technology	Innovative energy-efficient technology saves power up to 75%
Transfer Method	Store-and-Forward

## OTHERS

Certification	FCC, RoHS
Package Contents	16-Port 10/100Mbps Desktop/Rackmount Switch Power Cord Installation Guide Rackmount Kit Rubber Feet
Environment	Operating Temperature: 0°C~40°C (32°F~104°F); Storage Temperature: -40°C~70°C (-40°F~158°F); Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing