

MEDIA CONVERTER & MODULE

Standards and Protocols	IEEE 802.3ab, IEEE 802.3z, IEEE 802.3x
Basic Function	Full Duplex Flow Control (IEEE 802.3x) Extends fiber distance up to 0.5km for multi-mode fiber or up to 10km with single-mode fiber
Ports	1 x Gigabit SFP port 1 x 10/100/1000M RJ45 port (Auto MDI/MDIX)
Wave Length	Depends on the used SFP module
Network Media 1000BASE-X	Multi-mode/Single-mode SFP module
Network Media 1000BASE-T	UTP category 5, 5e, 6 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
LED Indicators	PWR, Link/Act
Dimensions (W*D*H)	3.7 x 2.9 x 1.1 in. (94 x 73 x 27 mm)
Power Supply	External Power Adapter (9VDC/ 0.6A)
Max Power Consumption	1.7 W
Safety & Emission	FCC, CE, RoHS
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing