

PRODUCT-DETAILS

UPS PowerValue 11T G2 6 kVA B2

UPS PowerValue 11 T G2 6 kVA B2



General Information

Extended Product Type	UPS PowerValue 11T G2 6 kVA B2
Product ID	4NWP100163R0002
EAN	7640169261954
Catalog Description	UPS PowerValue 11 T G2 6 kVA B2
Long Description	VFI online double conversion;6000W;8min;RS232;USB;COM slot

Additional Information

Apparent Power Output	6000 V·A
Battery Chemical Composition	Lead-Acid
Battery Runtime	5.5 minute [unit of time]
Battery Type	Portable
Battery Weight	2.5 kg
CN8	85044000
Communication Interface	USB, RS-232
Communication Protocol and Connection	SNMP
Connection Type	Fixed Connection
Country of Origin	China (CN)
Customs Tariff Number	85044000
Data Sheet, Technical Information	4NWD003884
Declaration of	4NWD003869

Conformity - CE

E-Number (Finland)	8408613
E-Number (Sweden)	5257252
EAN	7640169261954
ETIM 6	EC000382 - UPS
ETIM 7	EC000382 - UPS
Efficiency	Overall 94.10 % Economy Mode (Eco-Mode) 98.00 %
Environmental Information	No declaration needed
Harmonic Distortion	1.00 %
Input Voltage (U _{in})	208 V 220 V 230 V 240 V
Input Voltage Type	AC
Instructions and Manuals	4NWD003884
Invoice Description	UPS PowerValue 11 T G2 6 kVA B2
Minimum Order Quantity	1 piece
Number of Batteries	4
Number of Outputs	Fixed Connections 1
Number of Phases	Primary - 1 Secondary - 1
Object Classification Code	G
Options Provided	Auto shut down function Potential free switch contact Network-management
Output Voltage (U _{out})	208 V 220 V 230 V 240 V
Package Level 1 Depth / Length	598 mm
Package Level 1 EAN	7640169261954
Package Level 1 Gross Weight	65.3 kg
Package Level 1 Height	730 mm
Package Level 1 Units	1 piece
Package Level 1 Width	397 mm
Power Factor	1
Product Main Type	PowerValue 11T G2
Product Name	UPS
Product Net Depth / Length	452 mm
Product Net Height	589 mm
Product Net Weight	62.4 kg
Product Net Width	225 mm
Rated Frequency (f)	Primary 50 Hz Primary 60 Hz Secondary 50 Hz Secondary 60 Hz
Rated Output Power	6000 W
RoHS Date	0318
RoHS Information	4NWD003869
RoHS Status	Following EU Directive 2011/65/EU
Selling Unit of Measure	piece
Uninterruptible Power Supply Form Factor	Tower
Uninterruptible Power Supply Topology	On-Line Double Conversion

WEEE B2C / B2B

Business To Business

WEEE Category

4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

UPS, Power Conditioning and Power Distribution → UPS → Single-Phase UPS → PowerValue 11 T G2 IEC 230V

