

HARDWARE FEATURES

Standards and Protocols	IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab , IEEE 802.3x
Interface	24 10/100/1000Mbps RJ45 Ports (Auto Negotiation/Auto MDI/MDIX)
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) 100BASE-TX/1000BASE-T: UTP category 5, 5e or above cable (maximum 100m)
Fan Quantity	Fanless
Physical Security Lock	No
Power Supply	100-240VAC, 50/60Hz
Power Consumption	Maximum: 13.1W (220V/50Hz)
Dimensions (W x D x H)	11.6*7.1*1.7 in. (294*180*44 mm)
Mounting	Rack Mountable
Max Power Consumption	13.62W(220V/50Hz)
Max Heat Dissipation	46.44BTU/h

PERFORMANCE

Switching Capacity	48Gbps
Packet Forwarding Rate	35.7Mpps
MAC Address Table	8K
Jumbo Frame	10KB
Green Technology	Yes
Transfer Method	Store-and-Forward

OTHERS

Certification	FCC, RoHS
Package Contents	24-Port Gigabit Desktop/Rackmount Switch Power Cord Installation Guide Rackmount Kits Rubber Feet
Environment	Operating Temperature: 0°C~40°C (32°F~104°F); Storage Temperature: -40°C~70°C (-40°F~158°F); Operating Humidity: 10%~90% non-condensing; Storage Humidity: 5%~90% non-condensing