

To provide a better experience, we use cookies and similar tracking technologies to analyze traffic, personalize content and ads. By continuing to browse this website, you agree to our use of cookies and such technologies. [Learn more](#) [Don't show again](#)

| BUSINESS



TL-SG1016 V13

16-Port Gigabit Rackmount Switch

BUY NOW

HARDWARE FEATURES

Standards and Protocols	IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab , IEEE 802.3x, IEEE 802.1p
Interface	16 10/100/1000Mbps RJ45 Ports (Auto Negotiation/Auto MDI/MDIX)
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) 100BASE-TX/1000BASE-T: UTP category 5, 5e or above cable (maximum 100m)

HARDWARE FEATURES

Fan Quantity	Fanless
Physical Security Lock	No
Power Supply	100-240VAC, 50/60Hz
Dimensions (W x D x H)	17.3 x 7.1 x 1.7 in. (440*180*44 mm)
Mounting	19" Rack Mountable
Max Power Consumption	10.4W
Max Heat Dissipation	35.6BTU/h

PERFORMANCE

Switching Capacity	32Gbps
Packet Forwarding Rate	23.8Mpps
MAC Address Table	8K
Jumbo Frame	10KB
QoS	802.1p/DSCP QoS* *Only for V12 and later version
Green Technology	Yes
Transfer Method	Store-and-Forward

OTHERS

Certification	FCC, CE, RoHS
Package Contents	16-Port Gigabit Rackmount Switch Power Cord Installation Guide Rackmount Kits Rubber Feet
Environment	Operating Temperature: 0°C~40°C (32°F~104°F); Storage Temperature: -40°C~70°C (-40°F~158°F); Operating Humidity: 10%~90% non-condensing; Storage Humidity: 5%~90% non-condensing

Subscribe

Be The First To Get Exclusive Deals & News

Email Address

Subscribe

Let's Connect

[About Us](#)

[Press](#)

[Partners](#)

[Learning Center](#)

[Corporate Profile](#)

[News](#)

[Partner Program](#)

[Contact Us](#)

[Security Advisory](#)

[Training & Certifications](#)

[Careers at TP-Link](#)

[Blog](#)

[Deal Registration](#)

[Privacy Policy](#)

United States / English

Copyright © 2020 TP-Link Corporation Limited. All rights reserved.

