# MB4k

Handheld/Stand Cardioid Condenser Microphone

A price/performance leader, the MB4k cardioid condenser microphone is the Midnight Blues Series' introductory studio-quality microphone.





## Features

A price/performance leader, the MB4k cardioid condenser microphone is the Midnight Blues Series' introductory studio-quality microphone. With a condenser design for studio vocal and instrument applications, the microphone features: battery/phantom operation; rugged all-metal construction; soft-touch finish; extended response for smooth, natural sonic characteristics; corrosion-resistant contacts from gold-plated XLRM-type connector; on/off switch.

- · Introductory studio-quality microphone the clear price/performance leader
- · Condenser design for studio-quality vocal and instrument applications
- · Extended response for smooth, natural sonic characteristics
- Rugged all-metal construction and on/off switch

- · Soft-touch finish for a secure, comfortable grip and reduced mechanical noise
- · Battery/phantom operation for maximum versatility
- · Corrosion-resistant gold-plated XLRM-type connector

## Specifications

## Microphones

### Element

Fixed-charge back plate, permanently polarized condenser

## **Polar Pattern**

Cardioid

## Frequency Response

80 - 20,000 Hz

## Open Circuit Sensitivity

Phantom: -46 dB (5.0 mV) re 1V at 1 Pa - Battery: -48 dB (3.9 mV) re 1V at 1 Pa

## Maximum Input Sound Level

Phantom: 137 dB SPL, 1 kHz at 1% T.H.D. - Battery: 125 dB SPL, 1 kHz at 1% T.H.D.

## Dynamic Range

Phantom: 113 dB, 1 kHz at Max SPL - Battery: 101 dB, 1 kHz at Max SPL

## Signal-to-Noise Ratio

70 dB, 1 kHz at 1 Pa

## Phantom Power Requirements

11-52V DC, 2 mA typical

### **Battery Type**

1.5V AA/UM3

#### Battery Current/Life

0.4 mA/1200 hours typical

### Switches

On/off

## Weight

182 g

## Dimensions

8.10" (205.7 mm) long, 1.64" (41.7 mm) head diameter

## Output Connector

Integral 3-pin gold-plated XLRM-type

#### Accessories Included

AT8405a stand clamp for 5/8"-27 threaded stands; 5/8"-27 to 3/8"-16 threaded adapter; battery; soft protective pouch