BASIC INFORMATION

Type	UPS interative with AVR
Part Number (P/N)	POS2159
EAN	5600865271444
Model	ST-650VA LED
Color	Black
Type of sockets	Shuko
Number of sockets	2 sockets with power supply
Type of charge	Computers, Screens, POS
Autonomy	15-25 Min
Power	360W
Advantages	2 Shuko sockets Smart charger Up to 25 minutes of Autonomy
Datasheet	N/A

SPECIFICATIONS

Features

General	Color indicators LED lights Optimisation of reliability by microprocessor control AVR incorporated with boost and buck Intelligent management of the battery Fast-charging feature Mode off automatic charging Automatic reset feauture Cold start Audible and visual alarms
Sockets	2 sockets schuko with power supply
Display	YES - autonomy, consumption and voltage

Input

Voltage	230/120 VAC
Voltage break	170-280 VAC / 89-145 VAC
Frequency	50/60Hz +/- 10% (auto sensing)

Output

Voltage break	230VAC +/- 10%
Type of wave	Sine wave
Frequency	50/60Hz +/- 1%
Transfer time	≤ 6 ms, máx 10 ms

Battery

Type	Sealed Lead-Acid 12V, 7Ah
Charging time	90% da capacidade em 6 horas
Autonomy	15-25 minutos, dependendo dos equipamentos

Other

Dimensions (WxHxD)	320x90x150mm

Weight	5.4Kg
Temperature	Running: 0ºC~40ºC | Storage: -20ºC~60ºC
Humidity	0~90% without condensation
Noise	< 40dB
Certifications	CE, FCC, KC