

Audio-Technica U857 Specs

Microphone

Form Factor	Gooseneck
-------------	-----------

Sound Field	Mono
-------------	------

Capsule	Electret Condenser
---------	--------------------

Polar Pattern	Cardioid
---------------	----------

Orientation	End Address
-------------	-------------

Pad	<i>None</i>
-----	-------------

High-Pass Filter	Yes
------------------	-----

Gain Adjustment	Yes
-----------------	-----

Windscreen	Foam (Included)
------------	-----------------

Performance

Frequency Range	Cardioid Condenser: 30 Hz to 20 kHz
-----------------	---

Maximum SPL	135 dB SPL Peak (Phantom Power, 1 kHz, 1% THD)
-------------	--

Impedance	250 Ohms (Phantom Power)
Dynamic Range	115 dB A-Weighted (Phantom Power, 1 kHz, at Max SPL)
Signal-to-Noise Ratio	70 dB (1 kHz, at 1 Pa/94 dB SPL)

Connectivity

Output Connectors (Analog)	1 x XLR 3-Pin
----------------------------	----------------------

Power

Operating Voltage	11 to 52 V (Phantom Power)
-------------------	----------------------------

Physical

Color	Black
Mounting	Surface-Mount
Dimensions	L: 18" / L: 45.17 cm
