

# Specifications

Product type	Battery-powered PA speaker
Low/mid driver dimensions	10 "
Woofer size	254 mm
Woofer magnet	Ferrite
Woofer brand	Custom-made
HF driver dimensions	1 "
HF Driver Size	25.4 mm
HF driver magnet	Ferrite
HF driver brand	Custom-made
Amplifier	Class D
RMS	120 W
Peak power	480 W
Frequency response	55 - 18000 Hz
SPL (1W/1m)	96 dB
Max. SPL	115 dB
Protection circuits	over-current , overload protection , short circuit
Controls	AUX / MP3 switch , CD / Tape IN Level , Echo , high , low , Master Volume , Mic 1 Level , Mic 2 Level
Indicators	Charge/battery status , Power
<b>Media player</b>	
Supported media	Bluetooth , SD Card , USB stick
Supported formats	MP3 file , WAV-CD , WMA file
Media player controls	equalizer , Mode (Menu / Bluetooth /SD / USB) , Next Track , Play / Pause , Previous Track , Repeat , Stop

Media player display elements	Lighted multifunctional LC display
Line inputs	1
Line input connectors	2 x RCA , 2 x XLR , 3.5 mm jack , 6.3 mm jack
Mic inputs	2
Mic inputs	2 x XLR , 6.3 mm jack

## Wireless Unit

Transmission frequency range	863 - 865 MHz
Modulation Type	FM
Channels	16
Frequency Response Wireless Unit	50 - 17000 Hz
Controllers Wireless Unit	ASC , Mute Level (Squelch) , Power / Volume , Value Down , Value Up
Indicators Wireless Unit	AF (LED) , LED Display , RF (LED)
Connections Wireless Unit	nTNC for receiver antenna
RF Transmitter Power Output	10 mW
Bodypack weight	0.08 kg
Bodypack material	ABS plastic
Operating voltage	Switching power supply
Operating voltage	100 V - 120 V / 60 Hz , 220 V - 240 V AC / 50 Hz
Rechargeable batteries	12 V / 5 Ah
Cabinet material	Polypropylene
Cabinet construction	Bass Reflex
Width	415 mm
Height	525 mm
Depth	328 mm
Weight	16,5 kg
Other features	extendable handle , IR Remote for Media Player , Stand mount 36 mm , Transport casters , transport handle

