

# Specifications

Product type	PA loudspeaker
Type	Powered
Low/mid driver dimensions	10 "
Woofer size	254 mm
Woofer type	coaxial loudspeaker
Woofer magnet	Ferrite
Woofer brand	Custom-made
Woofer voice coil	2 "
Woofer voice coil (mm)	50.8 mm
HF driver dimensions	1 "
HF Driver Size	25.4 mm
HF driver magnet	Ferrite
HF driver brand	Custom-made
HF driver voice coil	1 "
HF Driver Voice Coil	25.4 mm
Amplifier	Class A/B
Dispersion (H x V)	75 x 75
RMS	150 W
Peak power	600 W
Frequency response	90 - 20000 Hz
Crossover frequency	3300 Hz
SPL (1W/1m)	99 dB
Max. SPL (continuous)	113 dB
Max. SPL (peak)	121 dB
Protection circuits	limiter , short circuit

Controls	On / Off , volume
Indicators	Limit , Power , Signal
Line Inputs	1
Line input connectors	6.3 mm jack , XLR
Line Outputs	1
Line output connectors	XLR
Operating voltage	transformer
Operating voltage	230 V AC / 50-60 Hz
Cabinet material	15 mm Plywood
Cabinet construction	Bass Reflex
Monitor angle	35 °
Width	380 mm
Depth	335 mm
Height	466 mm
Weight	15,3 kg
Features	ergonomically shaped insert handles