

# Specifications

Product type	PA subwoofer
Type	active
Low/mid driver dimensions	18 "
Woofer size	457.2 mm
Woofer magnet	Ferrite
Woofer brand	Custom-made
Woofer voice coil	4 "
Woofer voice coil (mm)	101.6 mm
Amplifier	Class D
RMS	800 W
Peak power	1600 W
Frequency response	35 - Low-Pass Hz
Max. SPL (peak)	135 dB
Protection circuits	DC , limiter , over voltage , short circuit
Input impedance	30000 Ohm(s)
Input sensitivity	0.3 V
Controls	Main level , Mode
Indicators	Limit , Mode , On , Protect (protection circuit engaged) , Signal
Line inputs	2
Line input connectors	6.3 mm jack , XLR
Line outputs	2
Line output connectors	XLR
Operating voltage	100 - 120 V / 50 - 60 Hz or 200 - 240 V / 50 - 60 Hz (automatic switching) , SMPS
Power Consumption (max.)	600 W

Operating Temperature	0 - 40 °C
Relative Humidity	< 80% (non-condensing)
Cabinet material	18 mm Plywood
Cabinet surface	Polyurea
Cabinet construction	Bass Reflex
Width	677 mm
Height	547 mm
Depth	740 mm
Weight	42,6 kg