

Specifications

Product type	PA loudspeaker
Type	passive
Low/mid driver dimensions	12 "
Woofer size	304.8 mm
Woofer magnet	Ferrite
Woofer brand	Custom-made
Woofer voice coil	2.5 "
Woofer voice coil (mm)	63.5 mm
Horn	BEM optimized CD Horn
HF driver dimensions	1 "
HF Driver Size	25.4 mm
HF driver magnet	Ferrite
HF driver brand	BMS
HF driver voice coil	1 "
HF Driver Voice Coil	25.4 mm
Dispersion (H x V)	90 x 50
Load rating (RMS)	400 W
Peak power	800 W
Frequency response	58 - 20000 Hz
SPL (1W/1m)	99 dB
Max. SPL	125 dB
Impedance	8 Ohm(s)
Protection circuits	HF Driver
Loudspeaker inputs	1
Speaker input connections	Speakon compatible

Loudspeaker outputs	1
Speaker output connections	Speakon compatible
Speakers per amplifier channel (DSP44/45K)	3
Cabinet material	15 mm Plywood
Cabinet surface	Polyurea
Cabinet construction	Bass Reflex
Monitor angle	54 °
Width	390 mm
Height	627 mm
Depth	377 mm
Weight	19,4 kg