

# Specifications

Product type	PA loudspeaker
Type	passive
Low/mid driver dimensions	10 "
Woofer size	254 mm
Woofer magnet	Ferrite
Woofer brand	Custom-made
Woofer voice coil	2 "
Woofer voice coil (mm)	50.8 mm
Horn	BEM optimized CD Horn
HF driver dimensions	1 "
HF Driver Size	25.4 mm
HF driver magnet	Ferrite
HF driver brand	BMS
HF driver voice coil	1 "
HF Driver Voice Coil	25.4 mm
Dispersion (H x V)	90 x 50
Load rating (RMS)	300 W
Peak power	600 W
Frequency response	65 - 20000 Hz
SPL (1W/1m)	96 dB
Max. SPL	121 dB
Impedance	8 Ohm(s)
Protection circuits	HF Driver
Loudspeaker inputs	1
Speaker input connections	Speakon compatible

Loudspeaker outputs	1
Speaker output connections	Speakon compatible
Speakers per amplifier channel (DSP44/45K)	4
Cabinet material	12 mm Plywood
Cabinet surface	Polyurea
Cabinet construction	Bass Reflex
Monitor angle	54 °
Width	325 mm
Height	527 mm
Depth	318 mm
Weight	11,5 kg