

Specifications

| | |
|---------------------------|--|
| Product type | PA loudspeaker |
| Type | active |
| Low/mid driver dimensions | 10 " |
| Woofer size | 254 mm |
| Woofer magnet | Ferrite |
| Woofer brand | Custom-made |
| Woofer voice coil | 2 " |
| Woofer voice coil (mm) | 50.8 mm |
| Horn | BEM optimized CD Horn |
| HF driver dimensions | 1 " |
| HF Driver Size | 25.4 mm |
| HF driver magnet | Ferrite |
| HF driver brand | BMS |
| HF driver voice coil | 1 " |
| HF Driver Voice Coil | 25.4 mm |
| Amplifier | Class D |
| Dispersion (H x V) | 90 x 50 |
| RMS | 300 W |
| Peak power | 600 W |
| Frequency response | 65 - 20000 Hz |
| Max. SPL (peak) | 127 dB |
| Protection circuits | Multiband limiter , over voltage , over-current , thermal overload |
| Input sensitivity | -9 dBu |
| Controls | 2 x gain , 2 x Mic/Line |
| Indicators | Limit , Mic , Mode , On , Protect (protection circui |

| | |
|------------------------|---|
| | t engaged) , Signal |
| Line inputs | 2 |
| Line input connectors | 6.3 mm jack , XLR |
| Line outputs | 1 |
| Line output connectors | XLR |
| Operating voltage | 100 - 120 V / 50 - 60 Hz or 200 - 240 V / 50 - 60 Hz (automatic switching) , Switching power supply |
| Operating Temperature | 0 - 40 °C |
| Relative Humidity | < 80% (non-condensing) |
| Cabinet material | 12 mm Plywood |
| Cabinet surface | Polyurea |
| Cabinet construction | Bass Reflex |
| Monitor angle | 54 ° |
| Width | 325 mm |
| Height | 527 mm |
| Depth | 318 mm |
| Weight | 12,7 kg |