

# Specifications

Weight	29,1 kg
Product type	PA Complete Systems
Color	Black
Max. SPL (continuous)	117 dB
Max. SPL (peak)	123 dB
Frequency response	45 - 19000 Hz
Dispersion (H x V)	60 x 60

## Subwoofer

Low/mid driver dimensions	8 "
Woofer size	203 mm
Woofer magnet	Ferrite
Woofer brand	Custom-made
Woofer voice coil	1.5 "
Woofer voice coil (mm)	38.1 mm
Cabinet construction	Bandpass
Cabinet material	MDF
Cabinet surface	painted
Subwoofer width	352 mm
Subwoofer height	430 mm
Subwoofer depth	434 mm
Subwoofer features	limiter , threaded flange M20 , transport handle

## Mid/Hi System

Midrange size	2 x 4 "
Midrange size	2 x 101.6 mm

Midrange magnet	Ferrite
Midrange brand	Custom-made
Midrange voice coil	1 "
Midrange voice coil	25.4 mm
Horn	radial
Tweeter dimensions	1 "
Tweeter dimensions (mm)	25.4 mm
Tweeter magnet	Ferrite
Tweeter brand	Custom-made
Tweeter voice coil	1 "
Tweeter voice coil (mm)	25.4 mm
Mid/Hi system impedance	4 Ohm(s)
Loudspeaker inputs	1
Speaker input connections	Speakon compatible
Cabinet construction mid/high	Closed
Mid/Hi system cabinet material	MDF
Mid/Hi system cabinet surface	painted
Mid/Hi system width	150 mm
Mid/Hi system height	350 mm
Mid/Hi system depth	170 mm
Mid/Hi system weight	4.2 kg
Mid/Hi system features	16 mm flange , metall front grille , transport handle

### Amplifier module (integrated in subwoofer)

Amplifier	Class A/B
Amplifier output system (RMS)	350 W
Amplifier output system (peak)	1400 W
Protection circuits	limiter , over-current , short circuit
Cooling	heat sink

Controls	input switch (MP3 / Hi-Z) , Line level , Main level , Mic level , MP3 / Hi-Z level , On / Off , Sub level , Subwoofer Phase Reverse
Indicators	Power , Protect (protection circuit engaged)
Operating voltage	220 V AC - 240 V AC
Line inputs	3
Line input connectors	6.3 mm jack , RCA , XLR
Mic inputs	1
Mic inputs	6.3 mm jack , XLR
MP3 inputs	1
MP3 input connectors	3.5 mm jack
Hi-Z inputs	1
Hi-Z input connectors	6.3 mm jack
Loudspeaker outputs	2
Speaker output connections	Speakon compatible