

# Specifications

Weight	29 kg
Product type	PA Complete Systems
Color	white
Max. SPL (continuous)	117 dB
Frequency response	45 - 19000 Hz
Dispersion (H x V)	60 x 60

## Subwoofer

Low/mid driver dimensions	8 "
Woofer size	203.2 mm
Woofer magnet	Ferrite
Woofer brand	Custom-made
Cabinet construction	Bandpass
Cabinet material	15 mm MDF
Cabinet surface	texture paint
Subwoofer width	352 mm
Subwoofer height	430 mm
Subwoofer depth	434 mm

## Mid/Hi System

Midrange size	2 x 4 "
Midrange size	2 x 101.6 mm
Midrange magnet	Ferrite
Midrange brand	Custom-made
Tweeter dimensions	1 "
Tweeter dimensions (mm)	25.4 mm

Tweeter magnet	Ferrite
Tweeter brand	Custom-made
Mid/Hi system impedance	4 Ohm(s)
Loudspeaker inputs	1
Speaker input connections	Speakon compatible
Cabinet construction mid/high	Closed
Mid/Hi system cabinet material	12 mm MDF
Mid/Hi system cabinet surface	texture paint
Mid/Hi system width	144 mm
Mid/Hi system height	350 mm
Mid/Hi system depth	170 mm
Mid/Hi system features	16 mm flange , 2 x M6 mounting points for wall mounting , Grilles for satellites included

### Amplifier module (integrated in subwoofer)

Amplifier	Class A/B
Amplifier output system (RMS)	350 W
Amplifier output system (peak)	1400 W
Protection circuits	limiter , overload , short circuit
Cooling	Aluminium heat sink
Controls	Power , Sub level , Subwoofer Phase Reverse , volume
Indicators	Power
Operating voltage	transformer
Operating voltage	220 V AC - 240 V AC, 50-60 Hz
Line inputs	2
Line input connectors	6.3 mm jack , RCA , XLR
Loudspeaker outputs	2
Speaker output connections	Speakon compatible Left/Right

