

Specifications

| | |
|-----------------------|---------------------|
| Weight | 63,2 kg |
| Product type | PA Complete Systems |
| Color | Black |
| Max. SPL (continuous) | 124 dB |
| Max. SPL (peak) | 135 dB |
| Frequency response | 32 - 20000 Hz |
| Dispersion (H x V) | 75 x 75 |

Subwoofer

| | |
|---------------------------|--|
| Low/mid driver dimensions | 18 " |
| Woofer size | 457.2 mm |
| Woofer magnet | Ferrite |
| Woofer brand | Custom-made |
| Woofer voice coil | 4 " |
| Woofer voice coil (mm) | 101.6 mm |
| Cabinet construction | Bass Reflex |
| Cabinet material | 18 mm Plywood |
| Cabinet surface | texture paint |
| Subwoofer width | 510 mm |
| Subwoofer height | 635 mm |
| Subwoofer depth | 710 mm |
| Subwoofer features | LD Systems "Evolutive" handles , threaded flange M20 |

Mid/Hi System

| | |
|---------------|--------|
| Midrange size | 10 " |
| Midrange size | 254 mm |

| | |
|--------------------------------|---|
| Midrange magnet | Ferrite |
| Midrange brand | Custom-made |
| Midrange voice coil | 2 " |
| Midrange voice coil | 50.8 mm |
| Horn | coaxial |
| Tweeter dimensions | 1 " |
| Tweeter dimensions (mm) | 25.4 mm |
| Tweeter magnet | Ferrite |
| Tweeter brand | Custom-made |
| Tweeter voice coil | 1 " |
| Tweeter voice coil (mm) | 25.4 mm |
| Mid/Hi system impedance | 4 Ohm(s) |
| Loudspeaker inputs | 1 |
| Speaker input connections | Speakon compatible |
| Cabinet construction mid/high | Closed |
| Mid/Hi system cabinet material | 15 mm Plywood |
| Mid/Hi system cabinet surface | texture paint |
| Mid/Hi system width | 300 mm |
| Mid/Hi system height | 460 mm |
| Mid/Hi system depth | 263 mm |
| Mid/Hi system features | ergonomically shaped insert handles , SM707 stand mount 36 mm |

Amplifier module (integrated in subwoofer)

| | |
|--------------------------------|--|
| Amplifier | Class D |
| Amplifier output system (RMS) | 1200 W |
| Amplifier output system (peak) | 4800 W |
| Protection circuits | limiter , overload , short circuit |
| Cooling | Convection |
| Controls | Main level , Power , Sub level , Subwoofer Phase |

| | |
|----------------------------|--|
| | Reverse |
| Indicators | Limit , On , Protect (protection circuit engaged) , Signal |
| Operating voltage | Switching power supply |
| Operating voltage | 100 V AC - 120 V AC, 50 - 60 Hz , 200 V AC - 240 V AC, 50 - 60 Hz (Automatic conversion) |
| Power consumption | 1200 VA |
| Line inputs | 2 |
| Line input connectors | 6.3 mm jack , RCA , XLR |
| Line output connectors | XLR |
| Loudspeaker outputs | 2 |
| Speaker output connections | Speakon compatible |