

Specifications

Weight	60,9 kg
Product type	PA Complete Systems
Color	Black
Max. SPL (continuous)	121 dB
Max. SPL (peak)	132 dB
Frequency response	35 - 19000 Hz
Dispersion (H x V)	90 x 40

Subwoofer

Low/mid driver dimensions	15 "
Woofer size	381 mm
Woofer magnet	Ferrite
Woofer brand	Custom-made
Woofer voice coil	3 "
Woofer voice coil (mm)	76.2 mm
Cabinet construction	Bass Reflex
Cabinet material	18 mm Plywood
Cabinet surface	texture paint
Subwoofer width	480 mm
Subwoofer height	570 mm
Subwoofer depth	635 mm
Subwoofer features	LD Systems "Evolutive" handles , threaded flange M20

Mid/Hi System

Midrange size	8 "
Midrange size	203.2 mm

Midrange magnet	Ferrite
Midrange brand	Custom-made
Midrange voice coil	1.5 "
Midrange voice coil	38.1 mm
Horn	CD horn
Tweeter dimensions	1 "
Tweeter dimensions (mm)	25.4 mm
Tweeter magnet	Ferrite
Tweeter brand	Custom-made
Tweeter voice coil	1 "
Tweeter voice coil (mm)	25.4 mm
Mid/Hi system impedance	4 Ohm(s)
Loudspeaker inputs	1
Speaker input connections	Speakon compatible
Cabinet construction mid/high	Closed
Mid/Hi system cabinet material	15 mm Plywood
Mid/Hi system cabinet surface	texture paint
Mid/Hi system width	275 mm
Mid/Hi system height	430 mm
Mid/Hi system depth	260 mm
Mid/Hi system features	ergonomically shaped insert handles , SM707 stand mount 36 mm

Amplifier module (integrated in subwoofer)

Amplifier	Class A/B
Amplifier output system (RMS)	700 W
Amplifier output system (peak)	2800 W
Protection circuits	limiter , overload , short circuit
Cooling	volume-controlled fan
Controls	Power , Sub level , Subwoofer Phase Reverse , v

Indicators	Volume Limit , on/off , Protect (protection circuit engaged) , Signal
Operating voltage	transformer
Operating voltage	220 V AC - 240 V AC
Power consumption	1000 VA
Line inputs	2
Line input connectors	6.3 mm jack , RCA , XLR
Line output connectors	XLR
Loudspeaker outputs	2
Speaker output connections	Speakon compatible