

# Specifications

Weight	27,5 kg
Product type	PA Complete Systems
Color	Black
Max. SPL (continuous)	115 dB
Max. SPL (peak)	126 dB
Frequency response	45 - 19000 Hz
Dispersion (H x V)	70 x 70

## Subwoofer

Low/mid driver dimensions	10 "
Woofer size	254 mm
Woofer magnet	Ferrite
Woofer brand	Custom-made
Woofer voice coil	2 "
Woofer voice coil (mm)	50.8 mm
Cabinet construction	Bass Reflex
Cabinet material	15 mm MDF
Cabinet surface	texture paint
Subwoofer width	345 mm
Subwoofer height	430 mm
Subwoofer depth	460 mm
Subwoofer features	LD Systems "Evolutive" handles , threaded flange M20

## Mid/Hi System

Midrange size	5.25 "
Midrange size	133.4 mm

Midrange magnet	Ferrite
Midrange brand	Custom-made
Midrange voice coil	1 "
Midrange voice coil	25.4 mm
Horn	radial
Tweeter dimensions	1 "
Tweeter dimensions (mm)	25.4 mm
Tweeter magnet	Neodymium
Tweeter brand	Custom-made
Tweeter voice coil	1 "
Tweeter voice coil (mm)	25.4 mm
Mid/Hi system impedance	4 Ohm(s)
Loudspeaker inputs	1
Speaker input connections	Speakon compatible
Cabinet construction mid/high	Closed
Mid/Hi system cabinet material	12 mm MDF
Mid/Hi system cabinet surface	texture paint
Mid/Hi system width	200 mm
Mid/Hi system height	300 mm
Mid/Hi system depth	230 mm
Mid/Hi system features	ergonomically shaped insert handles , Pole mount flange with 5° tilt

### Amplifier module (integrated in subwoofer)

Amplifier	Class A/B
Amplifier output system (RMS)	350 W
Amplifier output system (peak)	1400 W
Protection circuits	limiter , overload , short circuit
Cooling	Aluminium heat sink
Controls	Power , Sub level , Subwoofer Phase Reverse , v

Indicators	Volume
Operating voltage	Limit , Power , Signal
Operating voltage	transformer
Power consumption	220 V AC - 240 V AC
Line inputs	600 VA
Line input connectors	2
Loudspeaker outputs	6.3 mm jack , RCA , XLR
Speaker output connections	2
	Speakon compatible