

# Specifications

Product type	PA Complete Systems
System output (RMS):	460 W
Color	Black
Number of array satellites	4
Number of Smartlink adapters	1
Number of subwoofers	1
Max. SPL (continuous)	122 dB
Max. SPL (peak)	128 dB
Frequency response	47 - 20000 Hz
Dispersion (H x V)	110° horizontal, vertical (each satellite) 10
RMS	Subwoofer: 300 W , Array Satellites: 2 x 160 W
Peak power	Subwoofer: 1200 W , Array Satellites: 2 x 640 W
Amplifier	Class D
Protection circuits	DSP-based multiband limiter , overload , short circuit , thermal overload
Weight	26,5 kg
Accessories (included)	5-pin XLR system cable (10 m) , Distance bar , Power cord , Speaker cable CURV 500 CABLE 1 (2.2 m)

## Subwoofer

Low/mid driver dimensions	10 "
Woofer size	254 mm
Cabinet construction	Bass Reflex
Cabinet material	plywood
Cabinet surface	PA painting
Dimensions Subwoofer (W x H x D)	325 x 383 x 491 mm

Subwoofer weight	16.5 kg
Subwoofer features	3 ergonomic handles , Threaded flange M20

## Array Satellites

Mid/Hi system	MF: 1 x 4" / HF: 3 x 1" with WaveAhead® Technology / 16 ohms
Array Satellite Features	internal crossover , metal grille , WaveAhead® Technology
Array Satellite Material	Die-cast aluminium
Array Satellite Surface:	Powder coated
Array Satellite Dimensions (W x H x D)	122 x 122 x 122 mm
Array Satellite Weight	1.7 kg

## Smartlink® Adapter

Smartlink Adapter Features	2 x 16 mm pole mount socket , 2x M6 thread for optional wall mount
Smartlink Adapter Connectors	1 x Speakon-compatible , 1x Phoenix
Smartlink Adapter Material	Die-cast aluminium
Smartlink Adapter Surface	Powder coated
Smartlink Adapter Dimensions (W x H x D)	122 x 57 x 122 mm
Smartlink Adapter Weight	0.6 kg