

Specifications

Product type	PA Complete Systems
System output (RMS):	380 W
Color	Black
Number of array satellites	2
Number of Smartlink adapters	2
Number of subwoofers	1
Max. SPL (continuous)	116 dB
Max. SPL (peak)	122 dB
Frequency response	47 - 20000 Hz
Dispersion (H x V)	110° horizontal, vertical (each satellite) 10
RMS	Subwoofer: 300 W , Array Satellites: 2 x 160 W
Peak power	Subwoofer: 1200 W , Array Satellites: 2 x 640 W
Amplifier	Class D
Protection circuits	DSP-based multiband limiter , overload , short circuit , thermal overload
Weight	22,8 kg
Accessories (included)	2 x Speaker cable with terminal block CURV 500 CABLE 2 (3 m) , Power cord

Subwoofer

Low/mid driver dimensions	10 "
Woofer size	254 mm
Cabinet construction	Bass Reflex
Cabinet material	plywood
Cabinet surface	PA painting
Dimensions Subwoofer (W x H x D)	325 x 383 x 491 mm
Subwoofer weight	16.5 kg

Subwoofer features

16 DFX Presets , 3 ergonomic handles , 4 channel mixer , 4 System DSP Presets , Bluetooth , Threaded flange M20

Array Satellites

Mid/Hi system

MF: 1 x 4" / HF: 3 x 1" with WaveAhead® Technology / 16 ohms

Array Satellite Features

internal crossover , metal grille , WaveAhead® Technology

Array Satellite Material

Die-cast aluminium

Array Satellite Surface:

Powder coated

Array Satellite Dimensions (W x H x D)

122 x 122 x 122 mm

Array Satellite Weight

1.7 kg

Smartlink® Adapter

Smartlink Adapter Features

2 x 16 mm pole mount socket , 2x M6 thread for optional wall mount

Smartlink Adapter Connectors

1 x Speakon-compatible , 1x Phoenix

Smartlink Adapter Material

Die-cast aluminium

Smartlink Adapter Surface

Powder coated

Smartlink Adapter Dimensions (W x H x D)

122 x 57 x 122 mm

Smartlink Adapter Weight

0.6 kg