

Specifications

Product type	Line Arrays
Design	2-way speaker

Woofer characteristics

Low/mid driver dimensions	2 x 8 "
Woofer size	2 x 203.2 mm
Woofer magnet	Neodymium
Woofer brand	Custom-made

HF Driver characteristics

Horn	Waveguide
HF driver dimensions	2 x 1 "
HF Driver Size	2 x 25.4 mm
HF driver magnet	Neodymium
HF driver brand	Custom-made
HF driver voice coil	1.35 "
HF Driver Voice Coil	34.3 mm

other features

Dispersion (H x V)	100 x 10
Load rating (RMS)	500 W
HF driver RMS power	150 W
Frequency response	70 - 19000 Hz
Min. crossover frequency (Hz)	1600 Hz
SPL (1W/1m)	93 dB
Max. SPL	120 dB
Impedance	16 Ohm(s)

Loudspeaker protection	HF Driver
Tilt angle	0 / 1 / 2 / 3 / 4 / 5 / 6 °
Loudspeaker inputs	Neutrik Speakon, 4-pole
Speaker output connections	Neutrik Speakon, 4-pole
Cabinet material	18 mm Birch Plywood
Cabinet surface	Dura Coat LX Texture Paint
Cabinet construction	Bass Reflex
Width	740 mm
Height	247 mm
Depth	467 mm
Weight	27,5 kg
Features	ergonomically shaped insert handles , Integral rigging hardware