

Specifications

| | |
|--------------|---------------|
| Product type | Line Arrays |
| Design | 2-way speaker |

Woofer characteristics

| | |
|---------------------------|--------------|
| Low/mid driver dimensions | 2 x 4 " |
| Woofer size | 2 x 101.6 mm |
| Woofer type | Kevlar |
| Woofer magnet | Neodymium |
| Woofer brand | Custom-made |

HF Driver characteristics

| | |
|----------------------|-------------|
| Horn | Waveguide |
| HF driver dimensions | 1 " |
| HF Driver Size | 25.4 mm |
| HF driver magnet | Neodymium |
| HF driver brand | Custom-made |
| HF driver voice coil | 1.35 " |
| HF Driver Voice Coil | 34.3 mm |

other features

| | |
|-------------------------------|---------------|
| Dispersion (H x V) | 120 x 10 |
| Load rating (RMS) | 200 W |
| HF driver RMS power | 75 W |
| Frequency response | 80 - 19000 Hz |
| Min. crossover frequency (Hz) | 2100 Hz |
| SPL (1W/1m) | 90 dB |
| Max. SPL | 113 dB |

| | |
|----------------------------|---|
| Impedance | 16 Ohm(s) |
| Loudspeaker protection | HF Driver |
| Tilt angle | 0 / 2.5 / 5 / 7.5 ° |
| Loudspeaker inputs | Neutrik Speakon, 4-pole |
| Speaker output connections | Neutrik Speakon, 4-pole |
| Cabinet material | 18 mm Birch Plywood |
| Cabinet surface | Dura Coat LX Texture Paint |
| Cabinet construction | Bass Reflex |
| Width | 480 mm |
| Height | 139 mm |
| Depth | 261 mm |
| Weight | 9,6 kg |
| Features | Integral rigging hardware , Steel handles |