



SURT192XLBP



 ${\bf Extended-run\ battery\ systems\ provide\ flexible\ runtime\ to\ critical\ Smart-UPS\ applications.}$ Includes: Installation guide, User manual

Technical Specifications

Output	

Battery Output Voltage	192 V
Batteries & Runtime	

Battery type	Lead-acid battery
Included Battery Modules	4
Battery mounting	Stand alone battery stack
Expected Battery Life (years)	3 - 5
Replacement battery cartridge note	Replace all batteries in operation together (UPS internal and external batteries) all-at-once
RBC Quantity	2
Battery blocks per string	16

Physical

Maximum Height	130MM, 13.0CM
Maximum Width	432MM, 43.2CM
Maximum Depth	660MM, 66.0CM
Net Weight	90.91KG
Shipping weight	101.36KG
Shipping Height	413MM, 41.3CM
Shipping Width	600MM, 60.0CM
Shipping Depth	1000MM, 100.0CM
Color	Black
Units per Pallet	4.0

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0 - 15240meters

Conformance

Standard warranty	2 years repair or replace, optional on-site warranties available, optional extended warranties
	available

Sustainable Offer Status

RoHS	Compliant	
EOLI	Available in Documentation tab	
Proposition 65 Warning	Available in Documentation tab	

SIGN UP FOR EMAIL

I'd like to receive news and commercial info from Schneider Electric and its affiliates via electronic communication means such as email. For more details, please read our Privacy Policy.

Email I am a...

CONNECT WITH US WHO WE ARE

About APC Press APC Blog Investor Relations

Schneider Electric Data Centre Blog Careers

Sustainability Contact Us

FIND A RESELLER

Zip/Postal	de F	Find
------------	------	------

CATALOG KEYCODE













Terms & Conditions

Data Privacy and Cookie Policy

2021, APC by Schneider Electric