

SURT192RMXLBP2



Extended-run battery systems provide flexible runtime to critical Smart-UPS applications.

Includes: All required connectors, Rack mounting brackets, User manual



Technical Specifications

Output

Battery Output Voltage	192 V
-------------------------------	-------

Batteries & Runtime

Battery type	VRLA
Battery mounting	19 inch battery tray
Expected Battery Life (years)	3 - 5
RBC Quantity	4

Physical

Maximum Height	263MM, 26.3CM
Maximum Width	432MM, 43.2CM
Maximum Depth	739MM, 73.9CM
Net Weight	181.82KG
Shipping weight	220.45KG
Shipping Height	432MM, 43.2CM
Shipping Width	610MM, 61.0CM
Shipping Depth	1003MM, 100.3CM
Color	Black
Units per Pallet	1.0

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (Non-condensing) %

Operating Elevation	0 - 3048meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 (Non-condensing) %
Storage Elevation	0 - 15240meters

Conformance

Approvals	OSHDP
Standard warranty	2 years repair or replace

Sustainable Offer Status

RoHS	Compliant
PEP	Available in Documentation tab
EOL	Available in Documentation tab

SIGN UP FOR EMAIL

I'd like to receive news and commercial info from Schneider Electric and its affiliates via electronic communication means such as email. For more details, please read our [Privacy Policy](#).

OK

WHO WE ARE

- About APC
- Investor Relations
- Careers
- Sustainability

CONNECT WITH US

- Press
- APC Blog
- Schneider Electric Data Centre Blog
- Contact Us

FIND A RESELLER

CATALOG KEYCODE



[Terms & Conditions](#)

[Data Privacy and Cookie Policy](#)

2021, APC by Schneider Electric

