



SRT192BP2

RoHS

Extended-run battery systems provide flexible runtime to critical Smart-UPS applications.

Includes: Documentation CD, Installation guide, Warranty card

Technical Specifications

Output

Battery Output Voltage	+/- 192 V
------------------------	-----------

Batteries & Runtime

Battery type	Lead-acid battery
Battery mounting	Stand alone battery stack
Expected Battery Life (years)	3 - 5
RBC Quantity	2

Physical

Maximum Height	432MM, 43.2CM
Maximum Width	130MM, 13.0CM
Maximum Depth	683MM, 68.27CM
Net Weight	91.0KG
Shipping weight	101.5KG
Shipping Height	420MM, 42.0CM
Shipping Width	600MM, 60.0CM
Shipping Depth	1000MM, 100.0CM
Color	Black
Units per Pallet	1.0

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (Non-condensing) %

Operating Elevation	0 - 3048meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 (Non-condensing) %
Storage Elevation	0 - 15240meters

Conformance

Standard warranty	2 years repair or replace
--------------------------	---------------------------

Sustainable Offer Status

RoHS	Compliant
Proposition 65 Warning	Available in Documentation tab

SIGN UP FOR EMAIL

I'd like to receive news and commercial info from Schneider Electric and its affiliates via electronic communication means such as email. For more details, please read our [Privacy Policy](#).

Email
I am a... ▼

[Sign up](#)

WHO WE ARE

- [About APC](#)
- [Investor Relations](#)
- [Careers](#)
- [Sustainability](#)

CONNECT WITH US

- [Press](#)
- [APC Blog](#)
- [Schneider Electric Data Centre Blog](#)
- [Contact Us](#)

FIND A RESELLER

Zip/Postal Code	Find
-----------------	-------------

CATALOG KEYCODE

Enter Key Code	Go
----------------	-----------



[Terms & Conditions](#)

[Data Privacy and Cookie Policy](#)

2021, APC by Schneider Electric