



SRT72BP

RoHS

Extended-run battery systems provide flexible runtime to critical Smart-UPS applications.

Includes: Documentation CD, Installation guide

Technical Specifications

Output

Battery Output Voltage	72 V
------------------------	------

Batteries & Runtime

Battery type	Lead-acid battery
Expected Battery Life (years)	3 - 5
RBC Quantity	2

Physical

Maximum Height	432MM, 43.2CM
Maximum Width	85MM, 8.5CM
Maximum Depth	594MM, 59.4CM
Net Weight	33.9KG
Shipping weight	37.8KG
Shipping Height	239MM, 23.9CM
Shipping Width	599MM, 59.9CM
Shipping Depth	831MM, 83.1CM
Color	Black
Units per Pallet	6.0

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (Non-condensing) %
Operating Elevation	0 - 3048meters

Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 (Non-condensing) %
Storage Elevation	0 - 15240meters

Conformance

Standard warranty	2 years repair or replace
--------------------------	---------------------------

Sustainable Offer Status

RoHS	Compliant
Proposition 65 Warning	Available in Documentation tab

SIGN UP FOR EMAIL

I'd like to receive news and commercial info from Schneider Electric and its affiliates via electronic communication means such as email. For more details, please read our [Privacy Policy](#).

Email
I am a... ▼

Sign up

WHO WE ARE

- [About APC](#)
- [Investor Relations](#)
- [Careers](#)
- [Sustainability](#)

CONNECT WITH US

- [Press](#)
- [APC Blog](#)
- [Schneider Electric Data Centre Blog](#)
- [Contact Us](#)

FIND A RESELLER

Zip/Postal Code	Find
-----------------	------

CATALOG KEYCODE

Enter Key Code	Go
----------------	----



[Terms & Conditions](#)

[Data Privacy and Cookie Policy](#)

2021, APC by Schneider Electric