

SMX120BP

RoHS



Extended-run battery systems provide flexible runtime to critical Smart-UPS applications.

Includes: Installation guide, Rack mounting brackets



Technical Specifications

Output

Battery Output Voltage	120 V
-------------------------------	-------

Batteries & Runtime

Battery type	Lead-acid battery
Battery mounting	Enclosed battery cartridge
Expected Battery Life (years)	3 - 5
RBC Quantity	2
Battery blocks per string	10

Physical

Maximum Height	432MM, 43.2CM
Maximum Width	178MM, 17.8CM
Maximum Depth	483MM, 48.3CM
Net Weight	60.91KG
Shipping weight	65.45KG
Shipping Height	330MM, 33.0CM
Shipping Width	586MM, 58.6CM
Shipping Depth	633MM, 63.3CM
Color	Black
Units per Pallet	6.0

Environmental

Operating Temperature	0 - 40 °C
------------------------------	-----------

Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0 - 15240meters

Conformance

Standard warranty	2 years repair or replace
--------------------------	---------------------------

Sustainable Offer Status

RoHS	Compliant
Proposition 65 Warning	Available in Documentation tab

SIGN UP FOR EMAIL

I'd like to receive news and commercial info from Schneider Electric and its affiliates via electronic communication means such as email. For more details, please read our [Privacy Policy](#).

OK

WHO WE ARE

- About APC
- Investor Relations
- Careers
- Sustainability

CONNECT WITH US

- Press
- APC Blog
- Schneider Electric Data Centre Blog
- Contact Us

FIND A RESELLER

CATALOG KEYCODE



[Terms & Conditions](#)

[Data Privacy and Cookie Policy](#)

2021, APC by Schneider Electric