



## SMT2200RMI2UC

RoHS

Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other ...

Includes: Documentation CD, Rack mounting hardware, Rack mounting support rails, USB cable



## Technical Specifications

### Output

Max Configurable Power (Watts)	1.98kWatts / 2.2kVA
Output Voltage Note	Configurable for 220 : 230 or 240 nominal output voltage
Output Voltage Distortion	Less than 5 %
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz Sync to mains
Other Output Voltages	220, 240
Topology	Line interactive
Waveform type	Sine wave
Transfer Time	6 ms typical : 10 ms maximum

### Input

Input frequency	50/60 Hz +/- 3 Hz Auto-sensing
Input voltage range for main operations	151 - 302 Adjustable, 160 - 286V
Number of Power Cords	1
Other Input Voltages	220, 240

### Batteries & Runtime

Battery type	Lead-acid battery
Typical recharge time	3hour(s)
Replacement Battery	<a href="#">RRC43</a>

Replacement Battery	<a href="#">View Details</a>
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Battery Charge Power (Watts)	169 Watts
Runtime	<a href="#">View Runtime Graph</a> <a href="#">View Runtime Chart</a>
Efficiency	<a href="#">View Efficiency Graph</a>

## Communications & Management

Interface Port(s)	RJ-45 Serial, SmartSlot, USB
Control panel	Multifunction LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Available SmartSlot™ Interface Quantity	1

## Surge Protection and Filtering

Surge energy rating	375Joules
---------------------	-----------

## Physical

Maximum Height	86MM, 8.6CM
Maximum Width	432MM, 43.2CM
Maximum Depth	683MM, 68.3CM
Net Weight	42.31KG
Shipping weight	49.73KG
Shipping Height	254MM, 25.4CM
Shipping Width	600MM, 60.0CM
Shipping Depth	980MM, 98.0CM
Units per Pallet	8.0

## Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0 - 15240meters
Audible noise at 1 meter from surface of unit	55.0dBA
Online thermal dissipation	215.0BTU/hr

## Conformance

Approvals	CE, EAC, EN 60950, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE
Standard warranty	3 years repair or replace (excluding battery) and 2 years for battery

## Sustainable Offer Status

RoHS

Compliant

### SIGN UP FOR EMAIL

I'd like to receive news and commercial info from Schneider Electric and its affiliates via electronic communication means such as email. For more details, please read our [Privacy Policy](#).

Sign up

### WHO WE ARE

[About APC](#)

[Investor Relations](#)

[Careers](#)

[Sustainability](#)

### CONNECT WITH US

[Press](#)

[APC Blog](#)

[Schneider Electric Data Centre Blog](#)

[Contact Us](#)

### FIND A RESELLER

Find

### CATALOG KEYCODE

Go



[Terms & Conditions](#)

[Data Privacy and Cookie Policy](#)

2021, APC by Schneider Electric