

GENERAL

Warm-up time	25 seconds
First output speed: B/W	6.5 seconds
Continuous output speed	27 ppm
Memory: standard	2 GB
Memory: maximum	2 GB
ARDF capacity	100 sheets
Weight	46.5 kg
Dimensions: W x D x H	587 x 581 x 677 mm
Power source	220 - 240 V, 50 - 60 Hz
Laser classification	Class 1 Laser Product (IEC60825 - 1:2014)

COPIER

Multiple copying	Up to 999 copies
Resolution	600 x 600 dpi
Zoom	From 25% to 400%

PRINTER

Printer language	PCL5e, PCL6, PostScript 3 (emulation)
Print resolution: maximum	600 x 600 dpi
Network interface: standard	Ethernet 10 base-T/100 base-TX/1000 base-T, USB2.0 Type B, Wireless LAN (IEEE 802.11 a/b/g/n), USB Host 2.0
Mobile printing capability	Apple AirPrint, Mopria®, Google Cloud Print
Network protocol	TCP/IP (IP v4, IP v6)

Windows® environments	Windows® 7, Windows® 8.1, Windows® 10, Windows® Server 2008, Windows® Server 2008R2, Windows® Server 2012, Windows® Server 2012R2, Windows® Server 2016, Windows® Server 2019
Mac OS environments	Macintosh OS X v10.8 - v10.11

SCANNER

Scanning: B/W	50 ipm
Scanning: full colour	50 ipm
Resolution: maximum	600 dpi
Bundled drivers	Network TWAIN

FAX

Compatibility	ITU-T (CCITT) G3
Transmission speed	3 seconds
Modem speed: maximum	33.6 Kbps

PAPER HANDLING

Recommended paper size - Bypass tray:	Custom Size paper,Width, Custom Size paper,Length
Recommended paper size	Duplex tray
Paper input: standard	500 sheets
Paper input: maximum	1,600 sheets
Paper output: standard	250 sheets
Paper weight - Trays:	52 - 105 g/m ²
Paper weight - Bypass:	52 - 216 g/m ²

ECOLOGY

Power consumption: max.	Less than 1,550 W
----------------------------	-------------------

Power consumption operation: B/W	500 W
-------------------------------------	-------

CONSUMABLES

Toner (regular yield)	4,000 prints
-----------------------	--------------

Toner (high yield)	12,000 prints
--------------------	---------------