

319 mm (12 9/16 in)

Enclosure

Enclosure type
Reflex port

Drivers

Bass

Driver type
Cone

Magnetically shielded driver.

Diameter

7350A SAM™ Studio Subwoofer Technical Specifications

System Specifications

Frequency Response

25 Hz - 150 Hz (± 3 dB)

Low cutoff -6dB
22 Hz

High cutoff -6dB
160 Hz

SPL

Short term max SPL
 ≥ 104 dB

Maximum short term sine wave SPL output averaged from 30 to 85 Hz, measured in half space at 1 meter.

Self-generated noise

Self-generated noise
 ≤ 5 dB

Self generated noise level in half space at 1 m on axis (A-weighted).

Weight

Weight
19 kg (41.9 lb)

Dimensions

Height
410 mm (16 5/32 in)

Width
350 mm (13 25/32 in)

Depth

319 mm (12 9/16 in)

Enclosure

Enclosure type
Reflex port

Drivers

Bass

Driver type
Cone

Magnetically shielded driver.

Diameter

7350A SAM™ Studio Subwoofer Technical Specifications

System Specifications

Frequency Response

25 Hz - 150 Hz (± 3 dB)

Low cutoff -6dB
22 Hz

High cutoff -6dB
160 Hz

SPL

Short term max SPL
 ≥ 104 dB

Maximum short term sine wave SPL output averaged from 30 to 85 Hz, measured in half space at 1 meter.

Self-generated noise

Self-generated noise
 ≤ 5 dB

Self generated noise level in half space at 1 m on axis (A-weighted).

Weight

Weight
19 kg (41.9 lb)

Dimensions

Height
410 mm (16 5/32 in)

Width
350 mm (13 25/32 in)

Depth

319 mm (12 9/16 in)

Enclosure

Enclosure type
Reflex port

Drivers

Bass

Driver type
Cone

Magnetically shielded driver.

Diameter

7350A SAM™ Studio Subwoofer Technical Specifications

System Specifications

Frequency Response

25 Hz - 150 Hz (± 3 dB)

Low cutoff -6dB
22 Hz

High cutoff -6dB
160 Hz

SPL

Short term max SPL
 ≥ 104 dB

Maximum short term sine wave SPL output averaged from 30 to 85 Hz, measured in half space at 1 meter.

Self-generated noise

Self-generated noise
 ≤ 5 dB

Self generated noise level in half space at 1 m on axis (A-weighted).

Weight

Weight
19 kg (41.9 lb)

Dimensions

Height
410 mm (16 5/32 in)

Width
350 mm (13 25/32 in)

Depth

319 mm (12 9/16 in)

Enclosure

Enclosure type
Reflex port

Drivers

Bass

Driver type
Cone

Magnetically shielded driver.

Diameter

7350A SAM™ Studio Subwoofer Technical Specifications

System Specifications

Frequency Response

25 Hz - 150 Hz (± 3 dB)

Low cutoff -6dB
22 Hz

High cutoff -6dB
160 Hz

SPL

Short term max SPL
 ≥ 104 dB

Maximum short term sine wave SPL output averaged from 30 to 85 Hz, measured in half space at 1 meter.

Self-generated noise

Self-generated noise
 ≤ 5 dB

Self generated noise level in half space at 1 m on axis (A-weighted).

Weight

Weight
19 kg (41.9 lb)

Dimensions

Height
410 mm (16 5/32 in)

Width
350 mm (13 25/32 in)

Depth

319 mm (12 9/16 in)

Enclosure

Enclosure type
Reflex port

Drivers

Bass

Driver type
Cone

Magnetically shielded driver.

Diameter

7350A SAM™ Studio Subwoofer Technical Specifications

System Specifications

Frequency Response

25 Hz - 150 Hz (± 3 dB)

Low cutoff -6dB
22 Hz

High cutoff -6dB
160 Hz

SPL

Short term max SPL
 ≥ 104 dB

Maximum short term sine wave SPL output averaged from 30 to 85 Hz, measured in half space at 1 meter.

Self-generated noise

Self-generated noise
 ≤ 5 dB

Self generated noise level in half space at 1 m on axis (A-weighted).

Weight

Weight
19 kg (41.9 lb)

Dimensions

Height
410 mm (16 5/32 in)

Width
350 mm (13 25/32 in)

Depth

319 mm (12 9/16 in)

Enclosure

Enclosure type
Reflex port

Drivers

Bass

Driver type
Cone

Magnetically shielded driver.

Diameter

7350A SAM™ Studio Subwoofer Technical Specifications

System Specifications

Frequency Response

25 Hz - 150 Hz (± 3 dB)

Low cutoff -6dB
22 Hz

High cutoff -6dB
160 Hz

SPL

Short term max SPL
 ≥ 104 dB

Maximum short term sine wave SPL output averaged from 30 to 85 Hz, measured in half space at 1 meter.

Self-generated noise

Self-generated noise
 ≤ 5 dB

Self generated noise level in half space at 1 m on axis (A-weighted).

Weight

Weight
19 kg (41.9 lb)

Dimensions

Height
410 mm (16 5/32 in)

Width
350 mm (13 25/32 in)

Depth

319 mm (12 9/16 in)

Enclosure

Enclosure type
Reflex port

Drivers

Bass

Driver type
Cone

Magnetically shielded driver.

Diameter

7350A SAM™ Studio Subwoofer Technical Specifications

System Specifications

Frequency Response

25 Hz - 150 Hz (± 3 dB)

Low cutoff -6dB
22 Hz

High cutoff -6dB
160 Hz

SPL

Short term max SPL
 ≥ 104 dB

Maximum short term sine wave SPL output averaged from 30 to 85 Hz, measured in half space at 1 meter.

Self-generated noise

Self-generated noise
 ≤ 5 dB

Self generated noise level in half space at 1 m on axis (A-weighted).

Weight

Weight
19 kg (41.9 lb)

Dimensions

Height
410 mm (16 5/32 in)

Width
350 mm (13 25/32 in)

Depth

Enclosure

Enclosure type
Reflex port

Drivers

Bass

Driver type
Cone

Magnetically shielded driver.

Diameter

