

Shure PGA31 Specs

Microphone

Form Factor	Headworn
Sound Field	Mono
Capsule	Electret Condenser
Polar Pattern	Cardioid
Pad	<i>None</i>
High-Pass Filter	<i>None</i>
Windscreen	Foam (Included)

Performance

Frequency Range	60 Hz to 20 kHz
Maximum SPL	145 dB SPL (3% THD, 1-Kilohm Load)
Impedance	600 Ohms at 1 kHz
Output Level	-50 dBV/Pa

Dynamic Range	117 dB (1 kHz, 1-Kilohm Load)
---------------	-------------------------------

Signal-to-Noise Ratio	66 dB
-----------------------	-------

Equivalent Noise Level	28 dB A-Weighted (Typical)
------------------------	----------------------------

Connectivity

Output Connectors	1 x TA4/Mini XLR 4-Pin Female
-------------------	--------------------------------------

Cable Length	51.18" / 1.3 m
--------------	----------------

Power

Operating Voltage	5 to 10 V
-------------------	-----------

Physical

Color	Black
-------	-------

Mounting	Over-Ear (Double/Neckband)
----------	----------------------------

Weight	1.59 oz / 45 g
--------	----------------

Packaging Info

Package Weight

0.46 lb

Box Dimensions (LxWxH)

7.7 x 6.35 x 3.05"
