

# Shure 55SH II Specs

## Microphone

---

Form Factor	Stand/Boom Mount
-------------	------------------

---

Sound Field	Mono
-------------	------

---

Operating Principle	Pressure Gradient
---------------------	-------------------

---

Capsule	Dynamic
---------	---------

---

Polar Pattern	Cardioid
---------------	----------

---

Orientation	Side Address
-------------	--------------

---

Circuitry	Solid-State
-----------	-------------

---

Pad	<i>None</i>
-----	-------------

---

High-Pass Filter	<i>None</i>
------------------	-------------

---

Tone Adjustment	<i>None</i>
-----------------	-------------

---

Indicators	<i>None</i>
------------	-------------

---

On-Board Controls	On/Off
-------------------	--------

---

## Performance

---

Frequency Range	50 Hz to 15 kHz
Impedance	270 Ohms
Sensitivity	-58 dBV/Pa at 1 kHz

---

## Connectivity

---

Output Connectors (Analog)	<b>1 x</b> XLR 3-Pin (on Mic)
----------------------------	-------------------------------

---

## Physical

---

Color	Silver
Mounting	5/8"-27 Female (via Integrated Hardware)
Construction Material	Die-Cast Zinc
Dimensions	H: 7.4 x W: 2.19 x L: 3.06" / H: 188 x W: 55.6 x L: 77.8 mm (with Mount)
Weight	1.37 lb / 0.62 kg

---

## Packaging Info

---

Package Weight

1.79 lb

---

Box Dimensions (LxWxH)

10.15 x 4.95 x 3.3"

---