

Technical specifications

Product	
Part Number	D2G-DP2D-IF
Connectivity	
Video Input	Connectors: 1x DisplayPort
Video Output	Connectors: 2 x DVI-D (digital only outputs)
Multi-Unit Support	Yes (available under Windows only)
Performance	
Video Output Resolutions	DVI 3840x1200 (2x 1920x1200)* * Maximum resolution is system and monitor type dependent
Video and Audio Processing	
Non-Rectangular/Artistic Video Walls	No
Clone Mode	Yes
HDCP Support	Yes
Physical	

Product Dimensions	3.8 (L) x 2.5 (W) x 1.1 (H) inches
Unit Weight	0.264 lbs / 120 g
Power Supply Unit	USB for power
Hardware & Software	
Hardware Included	One USB cable One DisplayPort to DisplayPort input cable Software CD
Accessories (sold separately)	Power Supply Kit (Part # GXM-PSKIT-IF)
Software	Matrox PowerDesk (free download)
General	
System Requirements	Single DisplayPort or Mini DisplayPort video output, or Thunderbolt port*, on a compatible system* Display Driver supporting 3072 x 768 or higher resolution Powered USB connector *Thunderbolt port connectivity is currently supported only with Mac systems. Windows support coming soon.

Supported Operating Systems (software)

Windows 10
Windows 10 x64
Windows 7
Windows 7 x64
Windows 8
Windows 8 x64
Windows 8.1
Windows 8.1 x64
Windows Server 2003
Windows Server 2003 x64
Windows Server 2008
Windows Server 2008 R2
Windows Server 2008 x64
Windows Server 2012
Windows Server 2012 R2
Windows Vista
Windows Vista x64
Windows XP
Windows XP x64

