Technical specifications

Product				
Part Number	M9128-E1024LAF			
Bus Interface	PCIe x16			
Form Factor	Card: Low profile/half length Bracket: ATX and low profile			
Connectivity				
Video Output	Formats: DisplayPort SL-DVI (requires additional adapter) Connectors: 2x DisplayPort			
Maximum Number of Cards per System	2			
Performance				
Maximum Video Resolutions	Support for custom resolutions; contact Matrox for details.			
Memory	1 GB DDR2			

Video Output Resolutions	DisplayPort: 2560x1600* *Max resolutions are per output Support for Custom Resolutions contact Matrox for specific requirements.			
Video and Audio Processing				
Bezel Management	Yes (available under Windows only)			
Physical				
Product Dimensions	6.6 (L) x 2.7 (H) inches 16.67 (L) x 6.86 (H) cm			
Cooling	Fanless			
Additional Features	Open GL 2.0 support			
	Unified driver package			
Hardware & Software				
Hardware Included	Low profile bracket			
Software	Matrox PowerDesk (free download)			

Main Software Features	Independent Desktop Mode Stretched Desktop Mode Clone Mode Pivot Mode Joined Adapter Mode* *Not available under Microsoft Windows 7 and Vista when M9188 is the additional card, except under Windows 7 XDDM mode.
G	General
Supported Operating Systems (software)	Windows 7 (32-bit, 64-bit) Windows 8.x (32/64 bit) Microsoft® Windows® 10 (32-bit, 64-bit; non-WHQL) Windows Embedded Standard 7 (32*/64 bit) Windows Server® 2003 (32/64bit) Windows Server 2008 R1 (32-bit, 64-bit) Windows Server 2016 Windows Server 2016 Windows Server® 2012 (32-bit, 64-bit) Windows Server® 2016 R2 Windows Server® 2019 Windows Vista® (32-bit, 64-bit) Windows XP (32-bit, 64-bit) Linux®* *M-Series cards support a wide range of Linux operating systems. Refer to the README file in the driver download section for compatible Linux distributions or contact Matrox directly.
EMC/EMI Device Class	Class B
Warranty	Three-year limited warranty with free telephone support