

TYPE	2-way near-field studio reference monitors
LOW FREQ. DRIVER	5 inch (127mm) Kevlar curved cone with high temperature voice coil and damped rubber surround. Magnetically shielded
HIGH FREQ. DRIVER	1 inch (25mm) magnetically shielded natural silk dome
FREQUENCY RESPONSE	52 Hz – 35 kHz
CROSSOVER FREQUENCY	2.5kHz
LOW FREQ. AMPLIFIER POWER	60W
HIGH FREQ. AMPLIFIER POWER	40W
MAXIMUM PEAK SPL	110 dB SPL - Full Bandwidth Pink Noise Measured
INPUT SENSITIVITY	-10dBU
INPUT CONNECTORS	1x XLR balanced input connector 1x TRS balanced/unbalanced input connector
INPUT IMPEDANCE	10k Ω balanced, 20k Ω unbalanced
POLARITY	Positive signal at + input produce outward LF cone displacement
PROTECTION	RF interference, output current limiting, over temperature, turn on/off transient, subsonic filter, external mains fuse
POWER	Voltage: 100–120V, 50/60 Hz / 220–240V, 50/60 Hz Consumption: 100W

FUSE	220–240V~ T1AL 250V / 100–120V~ T1.6AL 250V
CABINET	Vinyl-laminated high-acoustic-efficiency MDF
DIMENSIONS(WIDTH X DEPTH X HEIGHT)	6.9" x 7.8" x 10" / 176 x 197 x 254 mm
WEIGHT	12.3 lbs, 5.6kg