

Portable PA System

Speaker Configuration	32 x Full-Range Speaker Column
-----------------------	---------------------------------------

Number of Input Channels	3 (2 x Mono, 1 x Stereo)
--------------------------	--------------------------

Amplifier Power Rating	Speakers: 1 x 480 W
------------------------	--------------------------------------

Amplifier Class	Class-D
-----------------	---------

Speakers

Full-Range Driver	32 x 2" / 50.8 mm Cone
-------------------	-------------------------------

Magnet	Neodymium
--------	-----------

Signal Processing

Input Pad	<i>None</i>
-----------	-------------

EQ	HF Shelf LF Shelf
----	----------------------

Semi-Parametric EQ	<i>None</i>
--------------------	-------------

Effects	Reverb
---------	--------

Filters	<i>None</i>
---------	-------------

Performance

Frequency Response 40 Hz to 20 kHz

Coverage Angle 180° H x 0° V

Protections *None*

Connectivity

Audio I/O **2 x** Combo XLR-1/4" 3-Pin Female Balanced Mic/Line/Hi-Z Input
1 x 1/8" / 3.5 mm TRS Female Unbalanced Line Input
1 x 1/4" TRS Female Unbalanced Line Input
1 x 1/4" TRS Female Balanced Line Output
1 x XLR 3-Pin Male Balanced Line Output

Phantom Power +48 V

USB *None*

Network I/O *None*

Wireless Connectivity Bluetooth

Power

AC Input Power 100 to 240 VAC, 50 / 60 Hz

Physical

Dimensions	84.1 x 21.7 x 13.6" / 213.6 x 55.1 x 34.5 cm
------------	--

Weight	28.6 lb / 13 kg
--------	-----------------

Packaging Info

Package Weight	42.7 lb
----------------	---------

Box Dimensions (LxWxH)	47 x 17.5 x 9"
------------------------	----------------

Bose L1 PRO Series Sub2 Portable Bass Module Specs

Configuration	Active Subwoofer
---------------	------------------

Enclosure Type	Bass-Reflex Line Array Subwoofer/Subwoofer
----------------	--

Amplifier Power Rating	1000 W
------------------------	--------

Amplifier Class	Class-D
-----------------	---------

Drivers

MF Driver

None

LF Driver

18 x 10" / 457.2 x 254 mm Woofer

Connectivity

Audio I/O

2 x Combo XLR-1/4" 3-Pin Female Balanced Line Input
2 x XLR 3-Pin Male Balanced Line Output
1 x Proprietary Subwoofer Input
1 x Proprietary 3-Pin Subwoofer Thru

Network I/O

None

USB

None

Wireless Connectivity

Bluetooth

Signal Processing

EQ

None

Alignment Delay

None

Phase Adjustment

None

Power

AC Input Power

100 to 240 VAC, 50 / 60 Hz

Physical

Mounting

1 x M20 Pole Socket (Side)

Handles

1 x Top

Dimensions

to 27.221.7 x 12" / to 55.1 x 30.5 cm

Weight

51.7 lb / 23.5 kg

Packaging Info

Package Weight

60 lb

Box Dimensions (LxWxH)

31 x 25.5 x 15.25"
