

Specification

Liebert GXT RT+ - UPS - 2700 Watt - 3000 VA

Device Type	UPS - rack-mountable / external
Rack Size	2U
Weight	27.6 kg
Input Voltage	AC 230 V
Output Voltage	AC 220/230/240 V \pm 1%
Power Capacity	2700 Watt / 3000 VA
Input Connectors	1 x power IEC 60320 C14
Output connectors	6 x power IEC 60320 C13 1 x power IEC 60320 C19
Battery	Lead Acid - 9 Ah
Dimensions (WxDxH)	43.8 cm x 63.2 cm x 8.8 cm
Manufacturer Warranty	2-year warranty

Extended Specification

General

Device Type	UPS - rack-mountable / external
Height (Rack Units)	2U

Battery

Capacity	9 Ah
Technology	Lead Acid

Dimensions & Weight

Depth	63.2 cm
Height	8.8 cm
Weight	27.6 kg
Width	43.8 cm

Environmental Parameters

Humidity Range Operating	10 - 90% (non-condensing)
Max Operating Temperature	40 °C
Min Operating Temperature	0 °C

Manufacturer Warranty

Service & Support	Limited warranty - 2 years
-------------------	----------------------------

Miscellaneous

Cables Included	Power cable USB cable
Compliant Standards	CB, ISTA 2A, EN 61000-4-5:2005, IEC/EN 62040-1: 2014, IEC/EN 62040-2: 2006+AC:2006 Class A
Features	LCD display
Power Device	
Frequency Required	40 - 70 Hz

Power Device

Input Connectors	1 x power IEC 60320 C14
Input Voltage	AC 230 V
Input Voltage Range (Adjustable)	AC 120 - 300 V
Output Voltage	AC 220/230/240 V \pm 1%
Output Waveform	Sinewave
Power Capacity	2700 Watt / 3000 VA
Power Output Connectors Details	6 x power IEC 60320 C13 1 x power IEC 60320 C19
Surge Suppression	Yes
UPS Technology	On-line