

Vertiv Liebert GXT5 10 KVA / 10 kW 230V Rack/Tower UPS Specifications

Manu. Code	GXT5-10KIRT5UXLE
Weight (approx)	74500.00g
Product Type	<u>UPS</u>
Technical details	
Brand	<u>Vertiv</u>
Collection	
Collection Model	Vertiv GXT5 10 KVA / 10 kW 230V Rack/Tower UPS
Design	
Product colour	Black
Form Factor	Rackmount/Tower
Cooling type	Active
Display	LCD
Safety	IEC62040-1:2008
Ports & interfaces	
USB port	Y
AC outlet types	C13 coupler,C19 coupler,IEC 320,Terminal C13 coupler, C19 coupler, IEC 320, Terminal
Power plug	Terminal
AC outlets quantity	8 AC outlet(s)
RS-232 ports	1
Serial ports quantity	1
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Battery Capacity	9 Ah
Battery voltage	12 V
Typical backup time at full load	2 min
Typical backup time at half load	7 min
Battery recharge time(90%)	5 h
Battery recharge time (90%)	5 h
Hot-swap battery	Y
Power	
Power factor	1
Weight & dimensions	
Width	430 mm

Depth	630 mm
Height	217 mm
Weight	74.5 kg
Performance	
International Protection (IP) code	IP20
Features	
UPS topology	Double-conversion (Online)
Output power capacity	10000 VA
Output power	10000 W
Waveform	Pure sine
Input operation voltage (min)	176 V
Input operation voltage (max)	288 V
Input frequency	50/60 Hz
Output operation voltage (min)	230 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Output voltage regulation	3%
Number of input phases	1
Number of output phases	1
Single-phase input voltage supported	220,230,240 V
Efficiency	95%
Efficiency (On-line mode)	95%
Input power factor	0.99
Output power factor	1
Emergency Power Off (EPO)	Y
Overload capacity (5 minute)	125%
Overload capacity (1 minute)	150%
Power protection features	Overload

Rack capacity	5U
Audible alarm(s)	Y
Noise level	55 dB
Output Voltage	230 V
Operational conditions	
Operating relative humidity (H-H)	0 - 95%
Operating temperature (T-T)	0 - 40 C
Storage temperature (T-T)	-15 - 40 C
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Certificates	
Certification	CE, EMI/EMC/C-Tick EMC, ESD
RoHS compliance	Y
Technical details	
Sustainability certificates	RoHS
Packaging data	
Battery Type	VRLA
Number of Batteries Supported	16
Package height	520 mm
Package width	646 mm
Package depth	816 mm
Package weight	93 kg
MPN	GXT5-10KIRT5UXLE