

Model Configuration

Model	B400/DN
Print speed	up to 47 ppm
Recommended monthly print volume	Up to 15,000 pages
Duty cycle	Up to 150,000 images/month ^①
Processor speed	1.05 GHz
Print memory (standard)	2 GB standard
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, NFC Tap-to-Pair (optional: Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported))
Maximum print resolution	1200 x 1200 dpi
First-page-out time, printing	As fast as 4.7 seconds
Page Description Languages (PDL)	Adobe® PostScript® 3™, HP-GL, JPEG, PCL® 5e, 6, PDF, TIFF, XPS
Print features	Booklet printing, Collation, Custom page size, Fit-to-page, N-up, Scaling, Secure Print, Toner save mode, Watermarks
Mobile printing	<u>Apple® AirPrint™</u> , <u>Google Cloud Print™</u> , <u>Mopria®</u> , <u>Xerox® Print Service Plug-in for Android™</u> (optional: <u>Xerox® Mobile Print Cloud</u> , <u>Xerox® Mobile Print Solution</u> , <u>@PrintByXerox</u> , <u>WiFi Direct®</u> [with optional Wi-Fi Kit])

Model	B400/DN
Two-sided output	Standard
ENERGY STAR	ENERGY STAR® qualified
Warranty	One-year on-site
Price	\$499 ^①
	<div style="border: 1px solid red; padding: 5px; display: inline-block; margin-bottom: 10px;">ADD TO CART</div> <div style="border: 1px solid black; padding: 5px; display: inline-block;">OTHER WAYS TO BUY</div>

Print Drivers

OS support	HP UX® 11, HP UX® 11i, IBM AIX® 5, Mac OS® X 10.5 and later, Redhat Enterprise 4 and 5, Solaris 10, Solaris 9, Ubuntu®, Windows® 2003 Server, Windows® 2008 Server, Windows® 7, Windows® Vista, Windows® XP, Xerox Global Printer Driver, Xerox Mobile Express Driver
-------------------	---

Font capabilities

PostScript® fonts	144
PCL® fonts	82

Media Handling

Output capacity	250 sheets

Paper capacity	Tray (Multipurpose tray): 150 sheets Tray 1: 550 sheets Tray 2 (optional): 550 sheets Tray 3 (optional): 550 sheets Tray 4 (optional): 550 sheets
Paper size	Tray (Multipurpose tray): Custom sizes: 3 x 5 in. to 8.5 x 14 in. (76.2 x 127 mm to 216 x 356 mm) Tray 1: Custom sizes: 3 x 5 in. to 8.5 x 14 in. (76.2 x 127 mm to 216 x 356 mm) Tray 2 (optional): Custom sizes: 5.5 x 8.3 in. to 8.5 x 14 in. (139.7 x 210 mm to 216 x 356 mm) Tray 3 (optional): Custom sizes: 5.5 x 8.3 in. to 8.5 x 14 in. (139.7 x 210 mm to 216 x 356 mm) Tray 4 (optional): Custom sizes: 5.5 x 8.3 in. to 8.5 x 14 in. (139.7 x 210 mm to 216 x 356 mm)

Security

Security features	256-bit Encryption, Access controls, Audit log, Automatic Self-Signed Certificate Creation, Certificate Path Validation, Certificate Revocation Settings, Domain Filtering, FIPS 140-2, Firmware Verification, IP Address Filtering, Network authentication, Port Filtering, Role based permissions, SNMPv3, Secure Email, Secure Fax, Secure Print, Secure Scan, Security certificates, Smart Card Enablement Kit (CAC/PIV/.NET), TLS
--------------------------	--

Electrical

Power consumption	Operating: 565 W Standby: 46 W Power save: as low as 1.11 W
--------------------------	---

Operating Environment

Temperature (operating)	50 - 90 ° F (10 - 32 ° C)

Relative humidity (operating)	10 - 85 % RH (noncondensing)
--------------------------------------	------------------------------

Dimensions

Dimensions (WxDxH)	18.1 x 16.8 x 13.3 in. (459 x 426 x 339 mm)
Weight	30 lb (14 kg)

Certifications

Sustainability	<u>EPEAT</u> <u>ENERGY STAR®</u>
-----------------------	-------------------------------------