

Spec description

Supported media	
CF	Compact Flash card Type1 (512MB to 64GB)
SD	SD card (512MB to 2GB) SDHC card (4GB to 32GB)
USB	USB flash memory (521MB to 64GB)
Recording formats	
WAV	Stereo/Mono, 44.1k / 48k Hz, 16-bit
MP3	Stereo/Mono, 44.1k / 48k Hz, 64k to 320k bps
Playback formats	
WAV	Stereo/Mono, 44.1k / 48k Hz, 16/24-bit
MP3	Stereo/Mono, 44.1k / 48k Hz, 64k to 320k bps
Number of channels	2 mono (or 1 stereo)
Inputs/Outputs	
ANALOG INPUTS	
Connector	RCA Pin jack × 1 pair
Standard input level	-10dBV (0.316Vrms)
Maximum input level	+6dBV (2.0Vrms)
Minimum input level	-24dBV (0.06Vrms) or more
Input impedance	22k Ω
ANALOG OUTPUTS	
Connector	RCA Pin jack × 1 pair
Standard output level	-10dBV (0.316Vrms)
Maximum output level	+6dBV (2.0Vrms)
output impedance	200 Ω
PHONES	
Connector	1/4" (6.3mm) Stereo Phone jack × 1
Maximum output	45mW + 45mW (into 32 Ω load, 0.1% distortion)
DIGITAL INPUT	
Connector	RCA Pin jack × 1

Format	IEC60958-3 (S/PDIF)
Input frequency	32k to 48k Hz
DIGITAL OUTPUT	
Connector	RCA Pin jack × 1
Format	IEC60958-3 (S/PDIF)
CONTROL I/O	
REMOTE IN	for included Wired Remote Controller RC-SS2
Connector	1/8" (3.5mm) TRS jack × 1
REMOTE IN	for optional Remote Controllers RC-20 and RC 3F
Connector	2.5mm TRS jack × 1
KEYBOARD	
Connector	mini-DIN (PS/2) × 1
USB	
Connector	USB A-type × 1
Protocol	USB2.0 HIGH SPEED (480Mbps)
Power	AC100 – 240V, 50/60Hz
Power consumption	20W (110-240V)
Dimensions (W × H × D)	19.0" × 1.75" × 11.9" / 482.6 × 44.5 × 301 mm
Weight	7.5 lbs. / 3.4 kg
Operating temperature range	41°F to 95°F / 5°C to 35°C

Audio performance

Frequency response	20Hz to 20kHz ±0.5dB (JEITA)
S/N ratio	95dB or more (JEITA)
Dynamic range	95dB (JEITA)
Distortion	0.005% or less (JEITA)
Channel crosstalk	95dB (JEITA)