

Spec description

	CD-9010CF	CD-9010	CD-6010
General			
CD			
Support disk	CD-DA,CD-ROM ISO9660 Level1/2/ROMEO/JOLIET		
Playable format	Audio CD(CD-DA), WAV		Audio CD(CD-DA),WAV,MP3
CD-DA			
Sampling frequency	44.1kHz		
Bit rate	16bit		
WAV			
Sampling frequency	44.1/48kHz		32/44.1/48kHz
Bit rate	16/24bit		16bit
MP3			
Sampling frequency	-	-	32/44.1/48kHz
Bit rate	-	-	64-320kbps,VBR
CF			
File system	FAT32(4GB or more), FAT16(2GB or less)	-	-
File formats	BWF,WAV	-	-
Number of audio channels	2 channel		
ANALOG OUTPUT			
LINE OUTPUT (unbalanced)	-	-	RCA
Output impedance	-	-	Less than 200ohms
Nominal output level	-	-	-10dBV
Max output level	-	-	+6dBV
LINE OUTPUT (balanced)	XLR-3-32(1:GND,2:HOT,3:COLD)		
Output impedance	200ohms		100ohms
Nominal output level	+4dBu/-20dBu selectable		+4dBu
Max output level	+24dBu		+24dBu
Reference level	-9dBFs/-14dBFs/-16dBFs/-18dBFs/-20dBFs		-
MONITOR OUTPUT (balanced)	XLR-3-32(1:GND,2:HOT,3:COLD)		
Output impedance	200ohms		-
Nominal output level	+4dBu		-
Max output level	+24dBu		-
Reference level	-9dBFs/-14dBFs/-16dBFs/-18dBFs/-20dBFs		-
PHONES	6.3mm 1/4-inch stereo phone jack		
Max output level	45mW + 45mW (1kHz,THD0.1%,32ohm loaded)		
DIGITAL OUTPUT			
AES-3id	BNC	-	-
Compatible signal format	AES3-2003/AES-3id-2001	-	-
COAXIAL	-	RCA	
Compatible signal format	-	IEC60958-3(S/PDIF) / IEC60958-4(AES/EBU) Switchable	

XLR	-	XLR-3-32(1:GND,2:HOT,3:COLD)	
Compatible signal format	-	IEC60958-3(S/PDIF) / IEC60958-4(AES/EBU) Switchable	
MIX INPUTS(balanced)	XLR-3-31(1:GND,2:HOT,3:COLD)		-
Input impedance	10kohms		-
Nominal input level	+4dBu		-
Max input level	+24dBu		-
WORD SYNC			
IN(balanced)	BNC		-
Input voltage	5V TTL		-
Input impedance	75ohms(ON/OFF selectable)		-
Synchronization accuracy	+/- 100ppm		-
THRU	BNC		-
KEYBOARD			
USB	USB-A		-
Type	US/JAPANESE		-
CONTROL I/O	D-sub15-pin(SERIAL), D-sub37-pin(PARALLEL)		2.5mm TRS jack(REMOTE), D-sub9-pin(SERIAL), D-sub25-pin(PARALLEL)
Power	100V-240V,50-60Hz		
Power consumption	18W		12.5W
Size(W x H x D)mm	220 x 136.8 x 361.5		483 x 94 x 303
Weight	5.5kg	5.3kg	4.9kg

Audio performance			
Frequency response	20Hz-20kHz, ±0.5dB		
S/N ratio	Greater than 100dB (20kHz LPF, a-weighted)		Greater than 95dB
THD	Less than 0.005% (+22dBu, 1kHz, 20kHz LPF)		
Channel separation	Greater than 90dB (1kHz)		Greater than 95dB

RC-9010S			
General			
PHONES	6.3mm 1/4-inch stereo phone jack		
Max output level	45mW + 45mW (1kHz, THD 0.1%, 32ohms loaded)		
Speaker output	Monaural		
Max output	1W		
To player unit	D-sub15-pin		
Power	Supplied by main unit		
Power consumption	3.6W		
Size(W x H x D)mm	220 x 77.2 x 227.6		
Weight	2.4kg		

AK-S9010			
General			
Size(W x H x D)mm	257 x 855 x 589		
Weight	16.8kg		

AK-A9010

General

Size(W x H x D)mm

220 x 52 x 92

Weight

500g