

Spec description

Audio inputs	
MIC 1-2 INPUT (Balanced)	
Connectors	XLR 3-31 / 1/4" (6.3mm) TRS combo jack × 2 (1: GND, 2: HOT, 3: COLD) / (Tip: HOT, Ring: COLD, Sleeve: GND)
Nominal input level	
VOLUME knob at MAX	-65dBu
VOLUME knob at MIN	-30dBu
Input impedance	33k Ω
LINE INPUTS (Unbalanced)	
Connectors	RCA Pin jack × 10 pairs
Nominal input level	-10dBV
Maximum input level	10dBV
Input impedance	22k Ω
Audio outputs	
MAIN OUTPUTS (Unbalanced)	
Connectors	RCA Pin jack × 3 pairs
Rated output level	-10dBV
Maximum output level	6dBV
Output impedance	200 Ω
MAIN OUTPUTS (Balanced)	
Connectors	XLR 3-31 × 3 pairs (1: GND, 2: HOT, 3: COLD)
Rated output level	4dBu
Maximum output level	24dBu
Output impedance	200 Ω
MONITOR OUT	
Connectors	RCA Pin jack × 1 pair
Rated output level	-16 dBV
Maximum output level	0dBV
Output impedance	200 Ω

PHONES	
Connectors	1/4" (6.3mm) Stereo phone jack × 1
Maximum output	50mW + 50mW (into 32 Ω load)
Power	AC adapter (TASCAM PS-M1524)
Input voltage	AC 100 – 240V, 50/60Hz
Output voltage	DC 15V
Output current	2.4A
Power consumption	35W
Dimensions (W×H×D)	19.0" × 5.2" × 3.7" / 482 × 88 × 93.2 mm
Weight	5.5 lbs. / 2.5 kg
Accessory	AC adapter (TASCAM PS-M1524), Cord for AC adapter (JAPAN USA/EUROPE) × each1, Rackmount screw kit, Owner's Manual (including warranty)

Audio performance

Frequency response	20Hz to 20kHz
Distortion	0.03% or less
S/N Ratio	80dB
Crosstalk	65dB