

# Tascam US-2X2HR Specs

Form Factor	Tabletop
Display	<i>None</i>
Channels of I/O	<b>Analog:</b> 2 Inputs / 2 Outputs
Max Sample Rate/Resolution	192 kHz / 24-Bit
Number of Mic Preamps	2
Input Level Adjustment	<b>2 x</b> Knob
Solo/Mute	<i>None</i>
Pad	<i>None</i>
High-Pass Filter	<i>None</i>
Expansion Slots	<i>None</i>

## Connectivity

Analog Audio I/O	<b>2 x</b> Combo XLR-1/4" TRS Balanced/Unbalanced Mic/Line/Hi-Z Input (Front Panel) <b>2 x</b> 1/4" TRS Balanced Line Output
------------------	---

**1 x** 1/4" TRS Unbalanced Headphone Output (Front Panel)

---

Phantom Power +48 V, Selectable On/Off (Applied to All Inputs)

---

Digital Audio I/O *None*

---

Host Connection / USB **1 x** USB Type-C (USB 2.0)

---

USB (Non-Host) *None*

---

Sync I/O *None*

---

Network I/O *None*

---

MIDI I/O **1 x** DIN 5-Pin Input  
**1 x** DIN 5-Pin Output

---

Wireless Connectivity *None*

---

Memory Card Slot *None*

---

## Performance

---

Frequency Response

**Mic, Line Inputs:**

20 Hz to 20 kHz +0/-0.4 dB (at 44.1/48 kHz, JEITA)

20 Hz to 40 kHz +0/-0.4 dB (at 88.2/96 kHz, JEITA)

**Line Outputs:**

20 Hz to 20 kHz +0.2/-0.1 dB (at 44.1/48 kHz, JEITA)

20 Hz to 40 kHz +0.2/-0.4 dB (at 88.2/96 kHz, JEITA)

---

Gain/Trim Range

**Mic/Line/Hi-Z Inputs:**

56 dB

---

Max Input Level

**Mic Inputs:**

+9 dBu

**Line Inputs:**

+20 dBu

**Hi-Z Inputs:**

+10 dBV

---

Max Output Level

**Line Outputs:**

+20 dBu

---

Headphone Output Power

18 mW per Channel into 32 Ohms (0.1% THD)

---

Impedance

**Mic Inputs:**

2.2 Kilohms

**Line Inputs:**

10 Kilohms

**Hi-Z Inputs:**

≥ 1 Megohm

**Line Outputs:**

210 Ohms

---

SNR

**Mic Inputs:**

110 dB (A-Weighted, Min Gain)

**Line Inputs:**

108 dB (A-Weighted, Min Gain)

**Line Outputs:**

110 dB (A-Weighted, Max Gain)

---

THD+N

**Mic Inputs:**

0.0013% (1 kHz, Min Gain)

**Line Inputs:**

0.0011% (1 kHz, Min Gain)

**Line Outputs:**

0.0012% (1 kHz)

---

Crosstalk

≥ 95 dB (1 kHz)

---

EIN	-128 dBu
-----	----------

---

## Digital Audio

---

Sample Rates	44.1 / 48 / 88.2 / 96 / 176.4 / 192 kHz
--------------	---

---

Sample Rate Conversion	<i>None</i>
------------------------	-------------

---

Bit Depths	24-Bit
------------	--------

---

Sync Sources	Internal
--------------	----------

---

## Compatibility

---

OS Compatibility	macOS 10.13 / 11 or Later Windows 7 or Later iPadOS 13 or Later iOS 11 or Later
------------------	--

---

Included Software	Cubase LE
-------------------	-----------

---

Compatible Software (Not Included)	Any Core Audio (Mac) Compliant Software
------------------------------------	---

---

Included Plug-Ins	<b>Virtual Instruments:</b> SampleTank SE
-------------------	--

---

Supported Drivers/API & Plug-Ins	Core Audio (Mac) ASIO WDM
----------------------------------	---------------------------------

---

Processor Requirement	2 GHz or Better
RAM Requirements	2 GB
Mobile Device Compatibility	iPad iPhone
Required Hardware	Available USB 2.0 Port USB Cable (Included)
Internet Connection	Required for Registration, Software/Driver Download

## Power

Power Requirements	AC/DC Power Adapter (Not Included) or USB Bus Power
AC/DC Power Adapter	5 VDC, Center-Positive (Not Included)
Power Consumption	1.75 W

## Physical

Operating Temperature	41 to 95°F / 5 to 35°C
Dimensions	7.3 x 6.3 x 2.6" / 18.6 x 16 x 6.5 cm (Including Controls and Protrusions)
Weight	2.4 lb / 1.1 kg

# Packaging Info

---

Package Weight 3.215 lb

---

Box Dimensions (LxWxH) 8.4 x 8 x 4.1"

---