



	FLEX 15	FLEX 30	FLEX 50
Rated IP65	YES	YES	YES
Impedance 100v Bypass	8 Ω	8 Ω	8 Ω
100V Tappings Watts	15, 7.5, 3.75, 1.87	30, 15, 7.5, 3.75	50, 25, 12.5, 6.25
70V Tappings Watts	7.5, 3.75, 1.87, 0.93	15, 7.5, 3.75, 1.87	25, 12.5, 6.25, 3.12
Max Power @ 8 Ω / RMS	30 Watts	40 Watts	50 Watts
Sensitivity 1W/1M	88dB	89dB	90dB
Calculated SPL			
RMS	100dB	105dB	107dB
PEAK	106dB	111dB	113dB
Dispersion -6 dB Points H x V	60° x 60°	90° x 60°	90° x 60°
Frequency Response	100-20KHz	80-20KHz	50-20KHz
Speaker Drivers	4 Inch woofer 1 Inch tweeter	5 ¼ Inch woofer 1 Inch tweeter	6 ½ woofer 1 Inch tweeter
Product Dimensions W x D x H mm	123 x 121 x 196	159 x 152 x 252	191 x 182 x 304
Shipping Dimensions W x D x H mm	330 x 154 x 217	420 x 195 x 275	502 x 233 x 329
Shipping Weight Kg	4.0	5.5	7.3