



## SPECIFICATIONS

	<b>XRS8B/W</b>	<b>XRS10B/W</b>	<b>XRS12B/W</b>
<b>Impedance</b>	8 Ohms	8 Ohms	8 Ohms
<b>Power (Continuous, Program)</b>	100 W, 200 W	250 W, 500 W	300 W, 600 W
<b>Sensitivity (1 W / 1 M)</b>	92 dB	95 dB	97 dB
<b>Calculated max SPL (Continuous, Peak)</b>	112 dB, 118 dB	119 dB, 125 dB	121 dB, 128 dB
<b>Dispersion (-6 dB Points) (H x V)</b>	90° x 90°	90° x 90°	90° x 90°
<b>Frequency Response (-3 dB)</b>	65 Hz - 18 kHz	55 Hz - 18 kHz	50 Hz - 18 kHz
<b>Frequency Response (-10 dB)</b>	60 Hz - 20 kHz	50 Hz - 20 kHz	40 Hz - 20 kHz
<b>Connection</b>	4 pole twist lock connectors	4 pole twist lock connectors	4 pole twist lock connectors
<b>Components</b>	1 x 8" Woofer, 1 x 1.5" HF Driver	1 x 10" Woofer, 1 x 1.5" HF Driver	1 x 12" Woofer, 1 x 2" HF Driver
<b>Net Dimensions (W x D x H)</b>	277 x 257 x 400 mm (per single) (10.9" x 10.1" x 15.7")	321 x 308 x 464 mm (12.6" x 12.1" x 18.3")	415 x 382 x 620 mm (16.3" x 15.0" x 24.4")
<b>Shipping Dimensions (W x D x H)</b>	595 x 310 x 460 mm (per pair) (23.4" x 12.2" x 18.1")	375 x 355 x 535 mm (14.8" x 14" x 21.1")	465 x 435 x 680 mm (16.3" x 15.4" x 23.6")
<b>Net Weight</b>	6.5 kg (14.3 lbs) (per single)	10 kg (22 lbs)	18 kg (39.7 lbs)
<b>Shipping Weight</b>	15 kg (33.1 lbs) (per pair)	12 kg (26.5 lbs)	20 kg (44.1 lbs)



	<b>XRS8P</b>	<b>XRS10P</b>	<b>XRS12P</b>
<b>Calculated max SPL (Continuous, Peak)</b>	112dB, 118 dB	119 dB, 125 dB	121.8 dB, 127.8 dB
<b>Dispersion (-6 dB Points) (H x V)</b>	90° x 90°	90° x 90°	90° x 90°
<b>Frequency Response (-3 dB)</b>	65 Hz - 18 kHz	55 Hz - 18 kHz	50 Hz - 18 kHz
<b>Frequency Response (-10 dB)</b>	55 Hz - 18 kHz	50 Hz - 18 kHz	40 Hz - 20 kHz
<b>Amplifier Type</b>	Class AB	Class AB	Class AB
<b>Power Requirements (VAC)</b>	120/240 V, 50/60 Hz	120/240 V, 50/60 Hz	120/240V, 50/60 Hz
<b>Power Output</b>	100 W (LF) + 50 W (HF)	100 W (LF) + 50 W (HF)	300 W (LF) + 100 W (HF)
<b>Connection</b>	3 Pin XLR	3 Pin XLR	3 Pin XLR
<b>Components</b>	1 x 8" Woofer, 1 x 1.5" HF Driver	1 x 10" Woofer, 1 x 1.5" HF Driver	1 x 12" Woofer, 1 x 2" HF Driver
<b>Net Dimensions (W x D x H)</b>	277 x 257 x 400 mm (10.9" x 10.1" x 15.7")	321 x 308 x 464 mm (12.6" x 12.1" x 18.3")	415 x 382 x 620 mm (16.3" x 15.0" x 24.4")
<b>Shipping Dimensions (W x D x H)</b>	355 x 325 x 470 mm (14" x 12.8" x 18.5")	375 x 355 x 535 mm (14.8" x 14" x 21.1")	465 x 435 x 680 mm (16.3" x 15.4" x 23.6")
<b>Net Weight</b>	8.6 kg (19 lbs)	10.5 kg (23.1 lbs)	23 kg (51 lbs)
<b>Shipping Weight</b>	10.1 kg (22.3 lbs)	11.8 kg (26 lbs)	25.2 kg (55.6 lbs)



## SPECIFICATIONS

	<b>XRS60DV</b>	<b>XRS80DV</b>
<b>Impedance (Bypass)</b>	8 Ohms	8 Ohms
<b>Power (70 V, 100 V Tappings)</b>	7.5 W, 15 W, 30, 60 W	15 W, 37.5 W, 75 W
<b>Power (Bypass Continuous / Program)</b>	80 W, 160 W	100 W, 200 W
<b>Sensitivity (1 W / 1 M)</b>	92 dB	92 dB
<b>Calculated max SPL (Continuous, Peak)</b>	111 dB, 117 dB	112 dB, 118 dB
<b>Dispersion (-6 dB Points) (H x V)</b>	90° x 60°	90° x 90°
<b>Frequency Response (-3 dB)</b>	95 Hz - 18 kHz	65 Hz - 18 kHz
<b>Frequency Response (-10 dB)</b>	85 Hz - 20 kHz	60 Hz - 20 kHz
<b>Connection</b>	Captive Fly Lead	Captive Fly Lead
<b>Components</b>	1 x 6" Woofer 1 x 1" HF Driver	1 x 8" Woofer, 1 x 1.5" HF Driver
<b>Net Dimensions (W x D x H)</b>	225 x 200 x 325 mm (8.9" x 7.9" x 12.8")	277 x 257 x 400 mm (10.9" x 10.1" x 15.7")
<b>Shipping Dimensions (W x D x H)</b>	260 x 260 x 390 mm (10.2" x 10.2" x 15.4")	355 x 325 x 470 mm (14" x 12.8" x 18.5")
<b>Net Weight</b>	7 kg (15.4 lbs)	10 kg (22 lbs)
<b>Shipping Weight</b>	8.2 kg (18 lbs)	12 kg (26.5 lbs)



	<b>XRS100DV</b>	<b>XRS120DV</b>
<b>Impedance (Bypass)</b>	8 Ohms	8 Ohms
<b>Power (70 V, 100 V Tappings)</b>	37.5 W, 75 W, 150 W	37.5 W, 75 W, 150 W, 300 W
<b>Power (Bypass / Continuous, Program)</b>	250 W, 500 W	300 W, 600 W
<b>Sensitivity (1 W / 1 M)</b>	95 dB	97 dB
<b>Calculated max SPL (Bypass / Continuous, Peak)</b>	119 dB, 125 dB	121 dB, 127 dB
<b>Dispersion (-6 dB Points) (H x V)</b>	90° x 90°	90° x 90°
<b>Frequency Response (-3 dB)</b>	55 Hz - 18 kHz (8 Ohm Bypass)	50 Hz - 18 kHz (8 Ohm Bypass)
<b>Frequency Response (-10 dB)</b>	50 Hz - 20 kHz (8 Ohm Bypass)	40 Hz - 20 kHz (8 Ohm Bypass)
<b>Connection</b>	Captive Fly Lead	Captive Fly Lead
<b>Components</b>	1 x 10" Woofer, 1 x 1.5" HF Driver	1 x 12" Woofer, 1 x 2" HF Driver
<b>Net Dimensions (W x D x H)</b>	321 x 308 x 464 mm (12.6" x 12.1" x 18.3")	415 x 382 x 620 mm (16.3" x 15.0" x 24.4")
<b>Shipping Dimensions (W x D x H)</b>	375 x 355 x 535 mm (14.8" x 14" x 21.1")	465 x 435 x 680 mm (16.3" x 15.4" x 23.6")
<b>Net Weight</b>	16.5 kg (36.4 lbs)	22 kg (48.5 lbs)
<b>Shipping Weight</b>	18.5 kg (40.8 lbs)	24 kg (52.9 lbs)