



## SPECIFICATIONS

	<b>XRS8B/W</b>	<b>XRS10B/W</b>	<b>XRS12B/W</b>
<b>Impedance</b>	8 Ohms	8 Ohms	8 Ohms
<b>Power (Continuous, Program)</b>	100 W, 200 W	250 W, 500 W	300 W, 600 W
<b>Sensitivity (1 W / 1 M)</b>	92 dB	95 dB	97 dB
<b>Calculated max SPL (Continuous, Peak)</b>	112 dB, 118 dB	119 dB, 125 dB	121 dB, 128 dB
<b>Dispersion (-6 dB Points) (H x V)</b>	90° x 90°	90° x 90°	90° x 90°
<b>Frequency Response (-3 dB)</b>	65 Hz - 18 kHz	55 Hz - 18 kHz	50 Hz - 18 kHz
<b>Frequency Response (-10 dB)</b>	60 Hz - 20 kHz	50 Hz - 20 kHz	40 Hz - 20 kHz
<b>Connection</b>	4 pole twist lock connectors	4 pole twist lock connectors	4 pole twist lock connectors
<b>Components</b>	1 x 8" Woofer, 1 x 1.5" HF Driver	1 x 10" Woofer, 1 x 1.5" HF Driver	1 x 12" Woofer, 1 x 2" HF Driver
<b>Net Dimensions (W x D x H)</b>	277 x 257 x 400 mm (per single) (10.9" x 10.1" x 15.7")	321 x 308 x 464 mm (12.6" x 12.1" x 18.3")	415 x 382 x 620 mm (16.3" x 15.0" x 24.4")
<b>Shipping Dimensions (W x D x H)</b>	595 x 310 x 460 mm (per pair) (23.4" x 12.2" x 18.1")	375 x 355 x 535 mm (14.8" x 14" x 21.1")	465 x 435 x 680 mm (16.3" x 15.4" x 23.6")
<b>Net Weight</b>	6.5 kg (14.3 lbs) (per single)	10 kg (22 lbs)	18 kg (39.7 lbs)
<b>Shipping Weight</b>	15 kg (33.1 lbs) (per pair)	12 kg (26.5 lbs)	20 kg (44.1 lbs)